



***P*roperty *M*aintenance *C*ode**

**Village of Ashville,
Ohio**

Chuck Wise, Mayor

PREFACE

Origin

The International Code Council (ICC) was established in 1994 as a nonprofit organization dedicated to developing a single set of comprehensive and coordinated national model construction codes. The founders of the ICC are Building Officials and Code Administrators International, Inc. (BOCA), International Conference of Building Officials (ICBO), and Southern Building Code Congress International, Inc. (SBCCI). Since the early part of the last century, these nonprofit organizations developed the three separate sets of model codes used throughout the United States. Although regional code development has been effective and responsive to our country's needs, the time came for a single set of codes. The nation's three model code groups responded by creating the International Code Council and by developing codes without regional limitations the International Codes.

Purpose of the ICC

There are substantial advantages in combining the efforts of the existing code organizations to produce a single set of codes. Code enforcement officials, architects, engineers, designers and contractors can now work with a consistent set of requirements throughout the United States. Manufacturers can put their efforts into research and development rather than designing to three different sets of standards, and can focus on being more competitive in worldwide markets. Uniform education and certification programs can be used internationally. A single set of codes may encourage states and localities that currently write their own codes or amend the model codes to begin adopting the International Codes without technical amendments. This uniform adoption would lead to consistent code enforcement and higher quality construction. The code organizations can now direct their collective energies toward wider code adoption, better code enforcement and enhanced membership services. All issues and concerns of a regulatory nature now have a single forum for discussion, consideration and resolution. Whether the concern is disaster mitigation, energy conservation, accessibility, innovative technology or fire protection, the ICC provides a single forum for national and international attention and focus to address these concerns.

All of these codes are comprehensive and coordinated with each other to provide the appropriate package for adoption and use in the 21st Century.

Services of the ICC

The organizations that comprise the International Code Council offer unmatched technical, educational and informational products and services in support of the International Codes, with more than 250 highly qualified staff members at 16 offices throughout the United States and in Latin America. Some of the products and services readily available to code users include:

- Code application assistance
- Educational programs
- Certification programs
- Technical handbooks and workbooks
- Plan reviews
- Automated products
- Monthly magazines and newsletters
- Publication of proposed code changes
- Training and Informational videos

ICC Code Development

Any interested individual or group may submit a code change proposal and participate in the proceedings in which it and all other proposals are considered. This open debate and broad participation before a committee comprised of representatives from across the construction industry, including code regulators and construction industry representatives, ensures a consensus of the construction community in the decision-making process. A major advantage of ICC's consensus-based private-sector code development process is that it allows both the ICC code development committees and eligible voting members at the code change hearings to participate in establishing the results of each proposal. Voting members may either ratify the committee's recommendation or make their own recommendation. The results of all votes are published in the report of the ICC code development hearings.

Eligible voting members of each of the three model code groups review the recommendations of the ICC code development committee at their annual conference and determine the final action. Following consideration of all public comments, each proposal is individually balloted by the eligible voters. The final action on the proposals is based on the aggregate count of all votes cast. This important process ensures that the International Codes will reflect the latest technical advances and address the concerns of those throughout the industry in a fair and equitable manner. Please visit our [codes page](#).

The mission of the International Code Council is to promulgate a comprehensive and compatible regulatory system for the built environment, through consistent performance-based regulations that are effective, efficient and meet government, industry and public needs.

PUNDLE

ICC Publications

The ICC has developed and made available an impressive inventory of International Codes, including:

- International Building Code®
- International Energy Conservation Code®
- ICC Electrical Code®
- International Existing Building Code®
- International Fire Code®
- International Fuel Gas Code®
- International Mechanical Code®
- ICC Performance Code™
- International Plumbing Code®
- International Private Sewage Disposal Code®
- International Property Maintenance Code®
- International Residential Code®
- International Urban-Wildland Interface Code™
- International Zoning Code®

TABLE OF CONTENTS

<p>CHAPTER 1 ADMINISTRATION1</p> <p>ELECTRICAL</p> <p>Section 101 General1</p> <p>Section 102 Applicability1</p> <p>Section 103 Department of Property Maintenance Inspection2</p> <p>Section 104 Duties and Powers of the Code Official2</p> <p>Section 105 Approval3</p> <p>Section 106 Violations4</p> <p>Section 107 Notices and Orders4</p> <p>Section 108 Unsafe Structures and Equipment5</p> <p>Section 109 Emergency Measures6</p> <p>Section 110 Demolition6</p> <p>Section 111 Means of Appeal7</p> <p>CHAPTER 2 DEFINITIONS8</p> <p>Section 201 General8</p> <p>Section 202 General Definitions8</p> <p>CHAPTER 3 GENERAL REQUIREMENTS10</p> <p>Section 301 General10</p> <p>Section 302 Exterior Property Areas10</p> <p>Section 303 Exterior Structure11</p> <p>Section 304 Interior Structure12</p> <p>Section 305 Rubbish and Garbage13</p> <p>Section 306 Extermination13</p> <p>.....</p> <p>CHAPTER 4 LIGHT, VENTILATION AND OCCUPANCY LIMITATIONS</p> <p>Section 401 General14</p> <p>Section 402 Light14</p> <p>Section 403 Ventilation14</p> <p>Section 404 Occupancy Limitations15</p> <p>.....</p> <p>CHAPTER 5 PLUMBING FACILITIES AND FIXTURE REQUIREMENTS17</p> <p>Section 501 General17</p> <p>Section 502 Required Facilities17</p> <p>Section 503 Toilet Rooms17</p> <p>Section 504 Plumbing Systems and Fixtures17</p> <p>Section 505 Water System18</p> <p>Section 506 Sanitary Drainage System18</p> <p>Section 507 Storm Drainage18</p>	<p>CHAPTER 6 MECHANICAL & REQUIREMENTS19</p> <p>Section 601 General19</p> <p>Section 602 Heating Facilities19</p> <p>Section 603 Mechanical Equipment19</p> <p>Section 604 Electrical Facilities20</p> <p>Section 605 Electrical Equipment20</p> <p>Section 606 Elevators, Escalators and Dumbwaiters20</p> <p>Section 607 Duct Systems20</p> <p>CHAPTER 7 FIRE SAFETY REQUIREMENTS21</p> <p>Section 701 General21</p> <p>Section 702 Means of Egress21</p> <p>Section 703 Accumulations and Storage23</p> <p>Section 704 Fire Resistance Ratings23</p> <p>Section 705 Fire Protection Systems23</p> <p>CHAPTER 8 REFERENCED STANDARDS25</p> <p>APPENDIX Construction Board of Adjustment and Appeals29</p> <p>Section 190.1 Establishment29</p> <p>Section 190.2 Terms29</p> <p>Section 190.3 Member qualifications29</p> <p>Section 190.4 Quorum29</p> <p>Section 190.5 Secretary of the Board29</p> <p>Section 190.6 Codes enforced29</p> <p>Section 190.7 Basis for appeal29</p> <p>Section 190.8 Board authority29</p> <p>Section 190.9 Time limits and conditions29</p> <p>Section 190.10 Notice of appeal29</p> <p>Section 190.11 Establishment of rules29</p> <p>Section 190.12 Decisions29</p> <p>Section 190.13 Compensation29</p> <p>Section 190.14 Abolishment of previous boards29</p> <p>Section 190.15 Saving clause29</p> <p>Section 190.16 Severability29</p> <p>INDEX33</p>
---	--

1998 INTERNATIONAL PROPERTY MAINTENANCE CODE

Property Maintenance Code of the Village of Ashville, Ohio

Charles Wise, Mayor

As adopted by the Council of the Village of Ashville, Ohio
Year 2000

COPYRIGHT © 1998 BY INTERNATIONAL CODE COUNCIL, INC.

All rights reserved. Chapters 1 through 8, inclusive, of the Property Maintenance Code of the Village of Ashville designate and incorporate portions of the *ICC International Property Maintenance Code*, 1998 edition, a copyrighted work owned by the INTERNATIONAL CODE COUNCIL, INC. Without advance written permission from the copyright owner, no part of this book may be reproduced, distributed, or transmitted in any form or by any means, including, without limitation, electronic, optical, or mechanical means (by way of example, and not limitation, photocopying, or recording by or in an information storage and retrieval system). The Village of Ashville edition of this copyrighted work is by arrangement with BOCA International, Inc. For information on permission to copy material exceeding fair use, please contact: Chief Executive Officer, BOCA International, Inc., 4051 West Flossmoor Road, Country Club Hills, Illinois 60478, (708) 799-2300.



AMENDMENTS AND ADDITIONS COPYRIGHT © 2000 BY THE VILLAGE OF ASHVILLE, OHIO

All rights reserved. No amendments or additions made by the Village of Ashville, Ohio to the *ICC International Property Maintenance Code*, 1998 edition, as reproduced in this book, may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, recording or by an information storage and retrieval system without advance permission in writing from the Village of Ashville, Ohio. For information, address: Village of Ashville, Planning & Zoning and Village Council, 200 East Station Street, Ashville, Ohio 43103.

CHAPTER 1 ADMINISTRATION

SECTION 101 GENERAL

101.1 Title. These regulations shall be known as the Property Maintenance Code of the Village of Ashville, Ohio, hereinafter referred to as "this code."

101.2 Scope. The provisions of this code shall apply to all existing residential and nonresidential structures and all existing premises and constitute minimum requirements and standards for premises, structures, equipment, and facilities for light, ventilation, space, heating, sanitation, protection from the elements, life safety, safety from fire and other hazards, and for safe and sanitary maintenance; the responsibility of owners, operators and occupants; the occupancy of existing structures and premises, and for administration, enforcement and penalties.

101.3 Intent. This code shall be construed to secure its expressed intent, which is to ensure public health, safety and welfare insofar as they are affected by the continued occupancy and maintenance of structures and premises. Existing structures and premises that do not comply with these provisions shall be altered or repaired to provide a minimum level of health and safety as required herein.

101.4 Severability. If a section, subsection, sentence, clause or phrase of this code is, for any reason, held to be unconstitutional, such decision shall not affect the validity of the remaining portions of this code.

SECTION 102 APPLICABILITY

102.1 General. The provisions of this code shall apply to all matters affecting or relating to structures and premises, as set forth in Section 101. Where, in a specific case, different sections of this code specify different requirements, the most restrictive shall govern.

102.2 Maintenance. Equipment, systems, devices and safeguards required by this code or a previous regulation or code under which the structure or premises was constructed, altered or repaired shall be maintained in good working order. The requirements of this code are not intended to provide the basis for removal or abrogation of fire protection and safety systems and devices in existing structures. Except as otherwise specified herein, the owner or the owner's designated agent shall be responsible for the maintenance of buildings, structures and premises.

102.3 Application of other codes. Repairs, additions or alterations to a structure, or changes of occupancy, shall be done in accordance with the procedures and provisions of the building, plumbing and mechanical codes and NFPA 70. Nothing in this code shall be construed to cancel, modify or set aside any provision of the zoning code.

102.4 Existing remedies. The provisions in this code shall not be construed to abolish or impair existing remedies of the jurisdiction or its officers or agencies relating to the removal or demolition of any structure which is dangerous, unsafe and in-sanitary.

102.5 Workmanship. Repairs, maintenance work, alterations or installations which are caused directly or indirectly by the enforcement of this code shall be executed and installed in a workmanlike manner and installed in accordance with the manufacturer's installation instructions.

102.6 Historic buildings. The provisions of this code shall not be mandatory for existing buildings or structures designated by the state or local jurisdiction as historic buildings when such buildings or structures are judged by the code official to be safe and in the public interest of health, safety and welfare.

102.7 Referenced codes and standards. The codes and standards referenced in this code shall be those that are listed in Chapter 8 and considered part of the requirements of this code to the prescribed extent of each such reference. Where differences occur between provisions of this code and the referenced standards, the provisions of this code shall apply.

102.8 Requirements not covered by code. Requirements necessary for the strength, stability or proper operation of an existing structure or equipment, or for the public safety, health and general welfare, not specifically covered by this code, shall be determined by the code official.

SECTION 103 DEPARTMENT OF PROPERTY MAINTENANCE INSPECTION

103.1 General. The department of property maintenance inspection is hereby created and the executive official in charge thereof shall be known as the code official.

103.2 Appointment. The code official shall be appointed by the chief appointing authority of the jurisdiction; and the code official shall not be removed from office except for cause and after full opportunity to be heard on specific and relevant charges by and before the appointing authority.

103.3 Deputies. In accordance with the prescribed procedures of this jurisdiction and with the concurrence of the appointing authority, the code official shall have the authority to appoint a deputy code official, other related technical officers, inspectors and other employees.

103.4 Restriction of employees. An official or employee connected with the enforcement of this code, except one whose only connection is that of a member of the board of appeals established under the provisions of Section 111, shall not be engaged in, or directly or indirectly connected with, the furnishing of labor, materials or appliances for the construction, alteration or maintenance of a building, or the preparation of construction documents thereof, unless that person is the owner of the building; nor shall such officer or employee engage in any work that conflicts with official duties or with the interests of the department.

103.5 Liability. The code official, officer or employee charged with the enforcement of this code, while acting for the jurisdiction, shall not thereby be rendered liable personally, and is hereby relieved from all personal liability for any damage accruing to persons or property as a result of an act required or permitted in the discharge of official duties.

Any suit instituted against any officer or employee because of an act performed by that officer or employee in the lawful discharge of duties and under the provisions of this code shall be defended by the legal representative of the jurisdiction until the final termination of the proceedings. The code official or any subordinate shall not be liable for costs in an action, suit or proceeding that is instituted in pursuance of the provisions of this code; and any officer of the department of property maintenance inspection, acting in good faith and without malice, shall be free from liability for acts performed under any of its provisions or by reason of any act or omission in the performance of official duties in connection therewith.

103.6 Fees. A fee for activities and services performed by the department in carrying out its responsibilities under this code shall be in accordance with the fee schedule as is set forth from time to time by resolution of the Council of the Village of Ashville, Ohio.

SECTION 104 DUTIES AND POWERS OF THE CODE OFFICIAL

104.1 General. The code official shall enforce the provisions of this code.

104.2 Rule-making authority. The code official shall have authority as necessary in the interest of public health, safety and general welfare, to adopt and promulgate rules and procedures; to interpret and implement the provisions of this code; to secure the intent thereof; and to designate requirements applicable because of local climatic or other conditions. Such rules shall not have the effect of waiving structural or fire performance requirements specifically provided for in this code, or of violating accepted engineering methods involving public safety.

104.3 Inspections. The code official shall make all of the required inspections, or shall accept reports of inspection by approved agencies or individuals. All reports of such inspections shall be in writing and be certified by a responsible officer of such approved agency or by the responsible individual. The code official is authorized to engage such expert opinion as deemed necessary to report upon unusual technical issues that arise, subject to the approval of the appointing authority.

104.4 Right of entry. The code official is authorized to enter the structure or premises at reasonable times to inspect subject to constitutional restrictions on unreasonable searches and seizures. If entry is refused or not obtained, the code official is authorized to pursue recourse as provided by law.

104.5 Identification. The code official shall carry proper identification when inspecting structures or premises in the performance of duties under this code.

104.6 Notices and orders. The code official shall issue all necessary notices or orders to ensure compliance with this code.

104.7 Department records. The code official shall keep official records of all business and activities of the department specified in the provisions of this code. Such records shall be retained in the official records as long as the building or structure to which such records relate remains in existence, unless otherwise provided for by other regulations.

104.8 Coordination of inspections. Whenever in the enforcement of this code or another code or ordinance, the responsibility of more than one code official of the jurisdiction is involved, it shall be the duty of the code

officials involved to coordinate their inspections and administrative orders as fully as practicable so that the owners and occupants of the structure shall not be subjected to visits by numerous inspectors or multiple or conflicting orders. Whenever an inspector from any agency or department observes an apparent or actual violation of some provision of some law, ordinance or code not within the inspector's authority to enforce, the inspector shall report the findings to the code official having jurisdiction.

104.9 Enforcement Powers. The code official and the building official or their designees shall have the authority to enforce provisions of this code. When acting within the scope of their employment hereunder, they shall have the powers of a police officer of the Village, provided however, that under no circumstances shall they have the power to arrest.

SECTION 105 APPROVAL

105.1 Modifications. Whenever there are practical difficulties involved in carrying out the provisions of this code, the code official shall have the authority to grant modifications for individual cases, provided the code official shall first find that special individual reason makes the strict letter of this code impractical and the modification is in compliance with the intent and purpose of this code and that such modification does not lessen health, life and fire safety requirements. The details of action granting modifications shall be recorded and entered in the department files.

105.2 Alternative materials, methods and equipment. The provisions of this code are not intended to prevent the installation of any material or to prohibit any method of construction not specifically prescribed by this code, provided that any such alternative has been approved. An alternative material or method of construction shall be approved where the code official finds that the proposed design is satisfactory and complies with the intent of the provisions of this code, and that the material, method or work offered is, for the purpose intended, at least the equivalent of that prescribed in this code in quality, strength, effectiveness, fire resistance, durability and safety.

105.3 Required Testing. Whenever there is insufficient evidence of compliance with the provisions of this code, or evidence that a material or method does not conform to the requirements of this code, or in order to substantiate claims for alternative materials or methods, the code official shall have the authority to require tests as evidence of compliance to be made at no expense to the jurisdiction.

105.3.1 Test methods. Test methods shall be as specified in this code or by other recognized test standards. In the absence of recognized and accepted test methods, the code official shall approve the testing procedures.

105.3.2 Testing agency. All tests shall be performed by an approved agency.

105.3.3 Test reports. Reports of tests shall be retained by the code official for the period required for retention of public records.

105.4 Material and equipment reuse. Materials, equipment and devices shall not be reused unless such elements have been reconditioned and tested when necessary, placed in good and proper working condition and approved.

SECTION 106 VIOLATIONS

106.1 Unlawful acts. It shall be unlawful for a person, firm or corporation to be in conflict with or in violation of any of the provisions of this code.

106.2 Notice of violation. The code official shall serve a notice of violation or order in accordance with Section 107.

106.3 Prosecution of violation. If the notice of violation is not complied with, the code official shall institute the appropriate proceeding at law or in equity to restrain, correct or abate such violation, or to require the removal or termination of the unlawful occupancy of the structure in violation of the provisions of this code or of the order or direction made pursuant thereto.

106.4 Violation penalties. Any person who shall violate a provision of this code, or fail to comply therewith, or with any of the requirements thereof shall be prosecuted within the limits provided by state or local laws. Each day that a violations continues after due notice has been served shall be deemed a separate offense.

106.5 Abatement of violation. The imposition of the penalties herein prescribed shall not preclude the legal officer of the jurisdiction from instituting appropriate action to restrain, correct or abate a violation, or to prevent illegal occupancy of a building, structure or premises, or to stop an illegal act, conduct, business or utilization of the building, structure or premises.

SECTION 107 NOTICES AND ORDERS

107.1 Notice to owner or to person or persons responsible. Whenever the code official determines that

there has been a violation of this code or has grounds to believe that a violation has occurred, notice shall be given to the owner or the person or persons responsible therefore in the manner prescribed in Sections 107.2 and 107.3. Notices for condemnation procedures shall also comply with Section 108.3.

107.2 Form. Such notice prescribed in Section 107.1 shall:

1. Be in writing
2. Include a description of the real estate sufficient for identification;
3. Include a statement of the violation or violations and why the notice is being issued;
4. Include a correction order allowing a reasonable time to make the repairs and improvements required to bring the dwelling unit or structure into compliance with the provisions of this code; and
5. Inform the property owner of the right to appeal.

107.3 Method of service. Such notice shall be deemed to be properly served if a copy thereof is:

1. Delivered personally; or
2. Sent by certified or first-class mail addressed to the last known address; or
3. If the notice is returned showing that the letter was not delivered, a copy thereof shall be posted in a conspicuous place in or about the structure affected by such notice.

107.4 Penalties. Penalties for noncompliance with orders and notices shall be as set forth in Section 106.4.

107.5 Transfer of ownership. It shall be unlawful for the owner of any dwelling unit or structure who has received a compliance order or upon whom a notice of violation has been served to sell, transfer, mortgage, lease or otherwise dispose of to another until the provisions of the compliance order or notice of violation have been complied with, or until such owner shall first furnish the grantee, transferee, mortgagee or lessee a true copy of any compliance order or notice of violation issued by the code official and shall furnish to the code official a signed and notarized statement from the grantee, transferee, mortgagee or lessee, acknowledging the receipt of such compliance order or notice of violation and fully accepting the responsibility without condition for making the corrections or repairs required by such compliance order or notice of violation.

SECTION 108

UNSAFE STRUCTURES AND EQUIPMENT

108.1 General. When a structure or equipment is found by the code official to be unsafe, or when a structure is

found unfit for human occupancy, or is found unlawful, such structure shall be condemned pursuant to the provisions of this code.

108.1.1 Unsafe structures. An unsafe structure is one that is found to be dangerous to the life, health, property or safety of the public or the occupants of the structure by not providing minimum safeguards to protect or warn occupants in the event of fire, or because such structure contains unsafe equipment or is so damaged, decayed, dilapidated, structurally unsafe, or of such faulty construction or unstable foundation, that partial or complete collapse is possible.

108.1.2 Unsafe equipment. Unsafe equipment includes any boiler, heating equipment, elevator, moving stairway, electrical wiring or device, flammable liquid containers or other equipment on the premises or within the structure which is in such disrepair or condition that such equipment is a hazard to life, health, property or safety of the public or occupants of the premises or structure.

108.1.3 Structure unfit for human occupancy. A structure is unfit for human occupancy whenever the code official finds that such structure is unsafe, unlawful or, because of the degree to which the structure is in disrepair or lacks maintenance, is insanitary, vermin or rat infested, contains filth and contamination, or lacks ventilation, illumination, sanitary or heating facilities or other essential equipment required by this code, or because the location of the structure constitutes a hazard to the occupants of the structure or to the public.

108.1.4 Unlawful structure. An unlawful structure is one found in whole or in part to be occupied by more persons than permitted under this code, or was erected, altered or occupied contrary to law.

108.2 Closing of vacant structures. If the structure is vacant and unfit for human habitation and occupancy, and is not in danger of structural collapse, the code official is authorized to post a placard of condemnation on the premises and order the structure closed up so as not to be an attractive nuisance. Upon failure of the owner to close up the premises within the time specified in the order, the code official shall cause the premises to be closed through any available public agency or by contract or arrangement by private persons and the cost thereof shall be charged against the real estate upon which the structure is located and shall be a lien upon such real estate.

108.3 Notice. Whenever the code official has condemned a structure or equipment under the provisions of this section, notice shall be posted in a conspicuous place in or about the structure affected by such notice and served on the owner or the person or persons responsible for the structure or equipment in accordance with Section 107.3. If the notice pertains to equipment, it shall also be placed on the condemned equipment. The notice shall be in the form prescribed in Section 107.2.

108.4 Placarding. Upon failure of the owner or person responsible to comply with the notice provisions within the time given, the code official shall post on the premises or on defective equipment a placard bearing the word "Condemned" and a statement of the penalties provided for occupying the premises, operating the equipment or removing the placard.

108.5 Prohibited occupancy. Any person who shall occupy a placarded premises or shall operate placarded equipment, and any owner or any person responsible for the premises who shall let anyone occupy a placarded premises or operate placarded equipment shall be liable for the penalties provided by this code.

108.6 Removal of placard. The code official shall remove the condemnation placard whenever the defect or defects upon which the condemnation and placarding action were based have been eliminated. Any person who defaces or removes a condemnation placard without the approval of the code official shall be subject to the penalties provided by this code.

SECTION 109 EMERGENCY MEASURES

109.1 Imminent danger. When, in the opinion of the code official, there is imminent danger of failure or collapse of a building or structure which endangers life, or when any structure or part of a structure has fallen and life is endangered by the occupation of the structure, or when there is actual or potential danger to the building occupants or those in the proximity of any structure because of explosives, explosive fumes or vapors or the presence of toxic fumes, gases or materials, or operation of defective or dangerous equipment, the code official is hereby authorized and empowered to order and require the occupants to vacate the premises forthwith. The code official shall cause to be posted at each entrance to such structure a notice reading as follows: "This Structure Is Unsafe and Its Occupancy Has Been Prohibited by the Code Official." It shall be unlawful for any person to enter such structure except for the purpose of securing the structure, making the required repairs, removing the hazardous condition or of demolishing the same.

109.2 Temporary safeguards. Notwithstanding other provisions of this code, whenever, in the opinion of the code official, there is imminent danger due to an unsafe condition, the code official shall order the necessary work to be done, including the boarding-up of openings, to render such structure temporarily safe whether or not the legal procedure herein described has been instituted; and shall cause such other action to be taken as the code official deems necessary to meet such emergency.

109.3 Closing streets. When necessary for the public safety, the code official shall temporarily close structures and close, or order the authority having jurisdiction to close, sidewalks, streets, public ways and places adjacent to unsafe structures, and prohibit the same from being utilized.

109.4 Emergency repairs. For the purposes of this section, the code official shall employ the necessary labor and materials to perform the required work as expeditiously as possible.

109.5 Costs of emergency repairs. Costs incurred in the performance of emergency work shall be paid by the jurisdiction. The legal counsel of the jurisdiction shall institute appropriate action"against the owner of the premises where the unsafe structure is or was located for the recovery of such costs.

109.6 Hearing. Any person ordered to take emergency measures shall comply with such order forthwith. Any affected person shall thereafter, upon petition directed to the appeals board, be afforded a hearing as described in this code.

SECTION 110 DEMOLITION

110.1 General. The code official shall order the owner of any premises upon which is located any structure, which in the code official's judgment is so old, dilapidated or has become so out of repair as to be dangerous, unsafe, insanitary or otherwise unfit for human habitation or occupancy, and such that it is unreasonable to repair the structure, to demolish and remove such structure; or if such structure is capable of being made safe by repairs, to repair and make safe and sanitary or to demolish and remove at the owner's option; or where there has been a cessation of normal construction of any structure for a period of more than two years, to demolish and remove such structure.

110.2 Notices and orders. All notices and orders shall comply with Section 107.

110.3 Failure to comply. If the owner of a premises fails to comply with a demolition order within the time prescribed, the code official shall cause the structure to be demolished and removed, either through an available public agency or by contract or arrangement with private persons, and the cost of such demolition and removal shall be charged against the real estate upon which the structure is located and shall be a lien upon such real estate.

110.4 Salvage materials. When any structure has been ordered demolished and removed, the governing body or other designated officer under said contract or arrangement aforesaid shall have the right to sell the salvage and valuable materials at the highest price obtainable. The net proceeds of such sale, after deducting the expenses of such demolition and removal, shall be promptly remitted with a report of such sale or transaction, including the items of expense and the amounts deducted, for the person who is entitled thereto, subject to any order of a court. If such a surplus does not remain to be turned over, the report shall so state.

111.2 Membership of Board: The board of appeals shall consist of members who are qualified by experience and training to pass on matters pertaining to property maintenance and who are not employees of the jurisdiction. The code official shall be an ex-officio member but shall have no vote on any matter before the board. The board shall be appointed by chief appointing authority.

111.3 Notice of Meeting: The board shall meet upon notice from the chairman within ten days of the filing of an appeal, or at stated periodic meetings.

111.4 Open hearing All hearings before the board shall be open to the public. The appellant, appellant's representative, the code official and any person whose interests are affected shall be given an opportunity to be heard. A quorum shall consist of not less than two-thirds of the board membership.

111.5 Postponed hearing: When the full board is not present to hear an appeal, either the appellant or the appellant's representative shall have the right to request a postponement of the hearing.

111.6 Board decision The board shall modify or reverse the decision of the code official only by a concurring vote of a majority of the total number of appointed board member.

111.6.1 RESOLUTION: The decision of the board shall be recorded. Copies shall be furnished to the appellant and the code official.

111.6.2 ADMINISTRATION: The code official shall take immediate action in accord with the board decision.

111.7 COURT REVIEW: Any person, whether or not a previous party of the appeal, shall have the right to apply to

the appropriate court for a writ of certiorari to correct errors of law. Application for review shall be made in the manner and time required by law following the filing of the decision in the office of the Village Administrator and Village Clerk.

111.6 STAYS OF ENFORCEMENT: Appeals of notice and orders (other than Imminent Danger notices) shall stay the enforcement of the notice and order until the appeal is heard by the appeals board.

CHAPTER 2 DEFINITIONS

SECTION 201 GENERAL

201.1 Scope. Unless otherwise expressly stated, the following terms shall, for the purposes of this code, have the meanings shown in this chapter.

201.2 Interchangeability. Words stated in the present tense include the future; words stated in the masculine gender include the feminine and neuter; the singular number includes the plural and the plural the singular.

201.3 Terms defined in other codes. Where terms are not defined in this code and are defined in the building, fire prevention, zoning, plumbing or mechanical codes, ASME A 17.1 and NFPA 70, such terms shall have the meanings ascribed to them as in those codes.

201.4 Terms not defined. Where terms are not defined, through the methods authorized by this section, such terms shall have ordinarily accepted meanings such as the context implies.

201.5 Parts. Whenever the words “dwelling unit,” “dwelling,” “premises,” “building,” “rooming house,” “rooming unit” or “story” are stated in this code, they shall be construed as though they were followed by the words “or any part thereof.”

SECTION 202 GENERAL DEFINITIONS

APPROVED. Approved by the code official.

BASEMENT. That portion of a building which is partly or completely below grade.

BATHROOM. A room containing plumbing fixtures including a bathtub or shower.

BEDROOM. Any room or space used or intended to be used for sleeping purposes.

CODE OFFICIAL. The individual or designee who is charged with the enforcement and administration of the Building Code of the Village of Asheville.

CODE OFFICIAL. The Chief of the Department of Fire/Rescue Services or designee..

CONDEMN. To adjudge unfit for occupancy.

DWELLING UNIT. A single unit providing complete, independent living facilities for one or more persons, including permanent provisions for living, sleeping, eating, cooking and sanitation.

EXTERIOR PROPERTY. The open space on the premises and on adjoining property under the control of owners or operators of such premises.

EXTERMINATION. The control and elimination of insects, rats or other pests by eliminating their harborage places; by removing or making inaccessible materials that serve as their food; by poison spraying, fumigating, trapping or by any other approved pest elimination methods.

GARBAGE. The animal or vegetable waste resulting from the handling, preparation, cooking and consumption of food.

HABITABLE SPACE. Space in a structure for living, sleeping, eating or cooking. Bathrooms, toilet rooms, closets, halls, storage or utility spaces, and similar areas are not considered habitable spaces.

IMMINENT HAZARD. A condition which could cause serious or life-threatening injury or death at any time.

INFESTATION. The presence, within or contiguous to, a structure or premises of insects, rats, vermin or other pests.

LABELED. Devices, equipment, appliances, or materials to which has been affixed a label, seal, symbol or other identifying mark of a nationally recognized testing laboratory, inspection agency or other organization concerned with product evaluation that maintains periodic inspection of the production of the above-labeled items and by whose label the manufacturer attests to compliance with applicable nationally recognized standards.

LET FOR OCCUPANCY OR LET. To permit, provide or offer possession or occupancy of a dwelling, dwelling unit, rooming unit, building, premise or structure by a person who is or is not the legal owner of record thereof, pursuant to a written or unwritten lease, agreement or license, or pursuant to a recorded or unrecorded agreement of contract for the sale of land.

OCCUPANCY. The purpose for which a building or portion thereof is utilized or occupied.

OCCUPANT. Any individual living or sleeping in a building; or having possession of a space within a building.

OPENABLE AREA. That part of a window, skylight or door which is available for unobstructed ventilation and which opens directly to the outdoors.

OPERATOR. Any person who has charge, care or control of a structure or premises which is let or offered for occupancy.

OWNER. Any person, agent, operator, firm or corporation having a legal or equitable interest in the property; or recorded in the official records of the state, county or municipality as holding title to the property; or otherwise having control of the property, including the guardian of the estate of any such person, and the executor or administrator of the estate of such person if ordered to take possession of real property by a court.

PERSON. An individual, corporation, partnership or any other group acting as a unit.

PREMISES. A lot, plot or parcel of land including any structures thereon.

ROOMING HOUSE. A building arranged or occupied for lodging, with or without meals, for compensation and not occupied as a one- or two-family dwelling.

ROOMING UNIT. Any room or group of rooms forming a single habitable unit occupied or intended to be occupied for sleeping or living, but not for cooking purposes.

RUBBISH. Combustible and noncombustible waste materials, except garbage; the term shall include the residue from the burning of wood, coal, coke and other combustible materials, paper, rags, cartons, boxes, wood,

excelsior, rubber, leather, tree branches, yard trimmings, tin cans, metals, mineral matter, glass, crockery and dust and other similar materials.

STRUCTURE. That which is built or constructed or a portion thereof.

TENANT. A person, corporation, partnership or group, whether or not the legal owner of record, occupying a building or portion thereof as a unit.

TOILET ROOM. A room containing a water closet or urinal but not a bathtub or shower.

VENTILATION. The natural or mechanical process of supplying conditioned or unconditioned air to, or removing such air from, any space.

WORKMANLIKE. Executed in a skilled manner; e.g., generally plumb, level, square, in line, undamaged, and without marring adjacent work.

YARD. An open space on the same lot with a structure.

CHAPTER 3 GENERAL REQUIREMENTS

SECTION 301 GENERAL

301.1 Scope. The provisions of this chapter shall govern the minimum conditions and the responsibilities of persons for maintenance of structures, equipment and exterior property.

301.2 Responsibility. The owner of the premises shall maintain the structures and exterior property in compliance with these requirements, except as otherwise provided for in Sections 305 and 306. A person shall not occupy as owner-occupant or permit another person to occupy premises which are not in a sanitary and safe condition and which do not comply with the requirements of this chapter. Occupants of a dwelling unit are responsible for keeping in a clean, sanitary and safe condition that part of the dwelling unit or premises which they occupy and control.

301.3 Vacant structures and land. All vacant structures and premises thereof or vacant land shall be maintained in a clean, safe, secure and sanitary condition as provided herein so as not to cause a blighting problem or adversely affect the public health or safety.

SECTION 302 EXTERIOR PROPERTY AREAS

302.1 Sanitation. All exterior property and premises shall be maintained in a clean, safe and sanitary condition. The occupant shall keep that part of the exterior property which such occupant occupies or controls in a clean and sanitary condition.

302.1.1 Animal Carcasses. The occupant shall keep that part of the exterior property which such occupant occupies or controls free of any putrid, unsound, or unwholesome bones, meats, hides, skins of the whole or any part of a dead animal, fish, or fowl.

302.2 Grading and drainage. All premises shall be graded and maintained to prevent the erosion of soil and to prevent the accumulation of stagnant water thereon, or within any structure located thereon.

Exception: Approved retention areas and reservoirs.

302.3 Sidewalks and driveways. All sidewalks, walkways, stairs, driveways, parking spaces and similar areas shall be kept in a proper state of repair, and maintained free from hazardous conditions. Stairs shall comply with the requirements of Sections 303.10 and 702.9.

302.3.1 Duty to Clear Snow and Ice; Responsibility. The owner, occupant or tenant of every property fronting upon or alongside any street or highway in the Village is hereby required to remove or cause to be removed from all sidewalks in front of or abutting such property, within eight hours after snow has ceased to fall, a sufficient amount of snow and ice to leave a clear pathway at least thirty-six inches in width for the entire length of that portion of the sidewalk in front of and abutting such property. The pathway shall run parallel to the curb or building line of such sidewalk except where a sidewalk is less than thirty-six inches in width, sufficient snow and ice shall be removed within such time to leave a clear pathway wide enough to permit one pedestrian at a time to pass thereover. Snow or ice that has ceased to fall or to be formed after 10:00 p.m. may be removed at any time before 10: a.m. the next morning. The owner of property shall be responsible for conforming to the requirements of this section, where such property is occupied by such owner or is unoccupied. The tenant or occupant thereof shall be responsible where such property is occupied by such tenant or occupant only, and the owner shall be responsible where the property is a multiple-business or a multiple-dwelling property occupied by more than one tenant or occupant.

302.3.2 Deposit of Removed Snow. No person shall throw, cast or deposit snow required to be removed by Section 302.3.1 in the roadbed of the street or highway adjoining such property, but is required to deposit the same upon the sidewalk along and immediately inside the curb thereof.

302.3.3 Removal by Village in Event of Delinquency. In any case where the owner,

occupant or tenant fails, neglects or refuses to comply with any of the provisions of this article within the time limit prescribed therein, the Village authorities may proceed immediately to clear all snow and/or ice from the sidewalk of such delinquents, and to collect the expense thereof, with any additional amount allowed by law, from such owner, occupant or tenant, as the case may be. Such action may be in addition to any fine or penalty imposed under the provisions of this article.

302.4 Weeds. All premises and exterior property shall be maintained free from weeds or plant growth in excess of 10 inches (254 mm). All noxious weeds shall be prohibited. Weeds shall be defined as all grasses, annual plants and vegetation, other than trees or shrubs provided; however, this term shall not include cultivated flowers and gardens.

302.5 Rodent harborage. All structures and exterior property shall be kept free from rodent harborage and infestation. Where rodents are found, they shall be promptly exterminated by approved processes which will not be injurious to human health. After extermination, proper precautions shall be taken to eliminate rodent harborage and prevent reinfestation.

302.6 Exhaust vents. Pipes, ducts, conductors, fans or blowers shall not discharge gases, steam, vapor, hot air, grease, smoke, odors or other gaseous or particulate wastes directly upon abutting or adjacent public or private property or that of another tenant.

302.7 Accessory structures. All accessory structures, including detached garages, fences and walls, shall be maintained structurally sound and in good repair.

302.7.1 Gates which are required to be self-closing and self-latching in accordance with the building code shall be maintained such that the gate will positively close and latch when released from a still position of 6 inches (152 mm) from the gatepost.

302.8 Motor vehicles. Except as provided for in other regulations, no inoperative, unlicensed, currently unregistered or uninspected motor vehicle shall be parked, kept or stored on any premises, and no vehicle shall at any time be in a state of major disassembly, disrepair, or in the process of being stripped or dismantled.

Exceptions:

A vehicle of any type is permitted to undergo major overhaul, including body work, provided that such work is performed inside a structure or similarly enclosed area designed and approved for such purposes.

One inoperative, unlicensed currently unregistered or uninspected vehicle may be stored in a fully enclosed exterior structure which is maintained in good repair, structurally sound, and sanitary so as not to pose a threat to the public health, safety or welfare.

One inoperative, unlicensed, currently unregistered or uninspected motor vehicle may be stored under a carport which is maintained in good repair, structurally sound, and sanitary so long as the vehicle is completely covered with a vehicle cover specially manufactured specifically for this purpose.

302.9 Defacement of property. No person shall willfully or wantonly damage, mutilate or deface any exterior surface of any structure or building on any private or public property by placing thereon any marking, carving or graffiti.

It shall be the responsibility of the owner to restore said surface to an approved state of maintenance and repair.

302.10 Refrigerators and Freezers. All refrigerators and freezers which are no longer in active service shall have the doors removed or otherwise be secured to prevent access by any individual to the interior.

302.11 Junkyards. Except as provided for in other regulations, no premises shall be used or maintained as junk yards, or dumping grounds, or for the wrecking or disassembling of automobiles, trucks, tractors, or machinery of any kind, or of any of the parts thereof or for the storing or leaving of any machinery or equipment used by contractors or builders or by other persons.

**SECTION 303
EXTERIOR STRUCTURE**

303.1 General. The exterior of a structure shall be maintained in good repair, structurally sound and sanitary so as not to pose a threat to the public health, safety or welfare.

303.2 Protective treatment. All exterior surfaces, including but not limited to, doors, door and window frames, cornices, porches and trim, shall be maintained in good condition. Exterior wood surfaces, other than decay-resistant woods, shall be protected from the elements and decay by painting or other protective covering or treatment. Peeling, flaking and chipped paint shall be eliminated and surfaces repainted. All siding and masonry joints as well as those between the building envelope and the perimeter of windows, doors, and skylights shall be maintained weather resistant and water tight.

303.3 Street numbers. Each structure to which a street number has been assigned shall have such number displayed in a position easily observed and readable from the public way. All numbers shall be in Arabic numerals at least 3 inches (76 mm) high and ½ -inch (13 mm) stroke.

303.4 Structural members. All structural members shall be maintained free from deterioration, and shall be capable of safely supporting the imposed dead and live loads.

303.5 Foundation walls. All foundation walls shall be maintained plumb and free from open cracks and breaks and shall be kept in such condition so as to prevent the entry of rodents.

303.6 Exterior walls. All exterior walls shall be free from holes, breaks, loose or rotting materials; and maintained weatherproof and properly surface coated where required to prevent deterioration.

303.7 Roofs and drainage. The roof and flashing shall be sound, tight and not have defects that admit rain. Roof drainage shall be adequate to prevent dampness or deterioration in the walls or interior portion of the structure. Roof drains, gutters and downspouts shall be maintained in good repair and free from obstructions. Roof water shall not be discharged in a manner that creates a public nuisance.

303.8 Decorative features. All cornices, belt courses, corbels, terra cotta trim, wall facings and similar decorative features shall be maintained in good repair with proper anchorage and in a safe condition.

303.9 Overhang extensions. All canopies, marquees, signs, metal awnings, fire escapes, standpipes, exhaust

ducts and similar overhang extensions shall be maintained in good repair and be properly anchored so as to be kept in a sound condition. When required, all exposed surfaces of metal or wood shall be protected from the elements and against decay or rust by periodic application of weather-coating materials, such as paint or similar surface treatment.

303.10 Stair and walking surfaces. Every stair, ramp, balcony, porch, deck or other walking surface shall comply with the provisions of Section 702.9.

303.11 Stairways, decks, porches and balconies. Every exterior stairway, deck, porch and balcony, and all appurtenances attached thereto, shall be maintained structurally sound, in good repair, with proper anchorage and capable of supporting the imposed loads.

303.12 Chimneys and towers. All chimneys, cooling towers, smoke stacks, and similar appurtenances shall be maintained structurally safe and sound, and in good repair. All exposed surfaces of metal or wood shall be protected from the elements and against decay or rust by periodic application of weathercoating materials, such as paint or similar surface treatment.

303.13 Handrails and guards. Every handrail and guard shall be firmly fastened and capable of supporting normally imposed loads and shall be maintained in good condition.

303.14 Window, skylight and door frames. Every window, skylight, door and frame shall be kept in sound condition, good repair and weather tight.

303.14.1 Glazing. All glazing materials shall be maintained free from cracks and holes.

303.14.2 Openable windows. Every window, other than a fixed window, shall be easily openable and capable of being held in position by window hardware.

303.15 Insect screens. During the period from [May 1 to September 30](#), every door, window and other outside opening required for ventilation of habitable rooms, food preparation areas, food service areas, or any areas where products to be included or utilized in food for human consumption are processed, manufactured, packaged or stored, shall be supplied with approved tightly fitting screens of not less than 16 mesh per inch (16 mesh per

25 mm) and every swinging door shall have a self-closing device in good working condition.

Exception: Screen doors shall not be required where other approved means, such as air curtains or insect repellent fans, are employed.

303.16 Doors. All exterior doors, door assemblies and hardware shall be maintained in good condition. Locks at all entrances to dwelling units, rooming units and guestrooms shall tightly secure the door.

303.17 Basement hatchways. Every basement hatchway shall be maintained to prevent the entrance of rodents, rain and surface drainage water.

303.18 Guards for basement windows. Every basement window that is openable shall be supplied with rodent shields, storm windows or other approved protection against the entry of rodents.

SECTION 304 INTERIOR STRUCTURE

304.1 General. The interior of a structure and equipment therein shall be maintained in good repair, structurally sound and in a sanitary condition. Every occupant shall keep that part of the structure which such occupant occupies or controls in a clean and sanitary condition. Every owner of a structure containing a rooming house, a hotel, a dormitory, two or more dwelling units or two or more nonresidential occupancies, shall maintain, in a clean and sanitary condition, the shared or public areas of the structure and exterior property.

304.2 Structural members. All structural members shall be maintained structurally sound, and be capable of supporting the imposed loads.

304.3 Interior surfaces. All interior surfaces, including windows and doors, shall be maintained in good, clean and sanitary condition. Peeling paint, cracked or loose plaster, decayed wood, and other defective surface conditions shall be corrected.

304.4 Stairs and railings. All interior stairs and railings shall be maintained in sound condition and good repair.

304.5 Stairs and walking surfaces. Every stair, ramp, balcony, porch, deck or other walking surface shall comply with the provisions of Section 702.9.

304.6 Handrails and guards. Every handrail and guard shall be firmly fastened and capable of supporting normally imposed loads and shall be maintained in good condition.

304.7 Interior doors. Every interior door shall fit reasonably well within its frame and shall be capable of being opened and closed by being properly and securely attached to jambs, headers or tracks as intended by the manufacturer of the attachment hardware.

SECTION 305 RUBBISH AND GARBAGE

305.1 Accumulation of rubbish or garbage. All exterior property and premises, and the interior of every structure, shall be free from any accumulation of rubbish or garbage.

305.2 Disposal of rubbish. Every occupant of a structure shall dispose of all rubbish in a clean and sanitary manner by placing such rubbish in approved containers.

305.2.1 Rubbish storage facilities. The owner of every occupied premises shall supply approved covered containers for rubbish, and the owner of the premises shall be responsible for the removal of rubbish.

305.3 Disposal of garbage. Every occupant of a structure shall dispose of garbage in a clean and sanitary manner by placing such garbage in an approved garbage disposal facility or approved garbage containers.

305.3.1 Garbage facilities. The owner of every dwelling shall supply one of the following: an approved mechanical food waste grinder in each dwelling unit; an approved incinerator unit in the structure available to the occupants in each dwelling unit; or an approved leakproof, covered, outside garbage container.

305.3.2 Containers. The operator of every establishment producing garbage shall provide, and at all times cause to be utilized, approved leakproof containers provided with closefitting covers for the

storage of such materials until removed from the premises for disposal.

SECTION 306 EXTERMINATION

306.1 Infestation. All structures shall be kept free from insect and rodent infestation. All structures in which insects or rodents are found shall be promptly exterminated by approved processes that will not be injurious to human health. After extermination, proper precautions shall be taken to prevent reinfestation.

306.2 Owner. The owner of any structure shall be responsible for extermination within the structure prior to renting or leasing the structure.

306.3 Single occupant. The occupant of a one-family dwelling or of a single-tenant nonresidential structure shall be responsible for extermination on the premises.

306.4 Multiple occupancy. The owner of a structure containing two or more dwelling units, a multiple occupancy, a rooming house or a nonresidential structure shall be responsible for extermination in the public or shared areas of the structure and exterior property. If infestation is caused by failure of an occupant to prevent such infestation in the area occupied, the occupants shall be responsible for extermination.

306.5 Occupant. The occupant of any structure shall be responsible for the continued rodent and pest-free condition of the structure.

Exception: Where the infestations are caused by defects in the structure, the owner shall be responsible for extermination.

CHAPTER 4 LIGHT, VENTILATION AND OCCUPANCY LIMITATIONS

SECTION 401 GENERAL

401.1 Scope. The provisions of this chapter shall govern the minimum conditions and standards for light, ventilation and space for occupying a structure.

401.2 Responsibility. The owner of the structure shall provide and maintain light, ventilation and space conditions in compliance with these requirements. A person shall not occupy as owner-occupant, or permit another person to occupy, any premises that do not comply with the requirements of this chapter.

401.3 Alternative devices. In lieu of the means for natural light and ventilation herein prescribed, artificial light or mechanical ventilation complying with the building code shall be permitted.

SECTION 402 LIGHT

402.1 Habitable spaces. Every habitable space shall have at least one window of approved size facing directly to the outdoors or to a court. The minimum total glazed area for every habitable space shall be 8 percent of the floor area of such room. Wherever walls or other portions of a structure face a window of any room and such obstructions are located less than 3 feet (914 mm) from the window and extend to a level above that of the ceiling of the room, such window shall not be deemed to face directly to the outdoors nor to a court and shall not be included as contributing to the required minimum total window area for the room.

Exception: Where natural light for rooms or spaces without exterior glazing areas is provided through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but not less than 25 square feet (2.33 m²). The exterior glazing area shall be based on the total floor area being served.

402.2 Common halls and stairways. Every common hall and stairway, other than in one- and two-family dwellings, shall be lighted at all times with at least a 60-watt standard incandescent light bulb or equivalent for each 200 square feet (19 m²) of floor area, provided that the spacing between lights shall not be greater than 30 feet (9144 mm). Every exterior means of egress stairway, other than in one- and two-family dwellings, shall be illuminated with a minimum of 1 footcandle (11 lux) at floors, landings and treads.

402.3 Other spaces. All other spaces shall be provided with natural or artificial light sufficient to permit the maintenance of sanitary conditions, and the safe occupancy of the space and utilization of the appliances, equipment and fixtures.

SECTION 403 VENTILATION

403.1 Habitable spaces. Every habitable space shall have at least one openable window. The total openable area of the window in every room shall be equal to at least 45 percent of the minimum glazed area required in Section 402.1.

Exception: Where rooms and spaces without openings to the outdoors are ventilated through an adjoining room, the unobstructed opening to the adjoining room shall be at least 8 percent of the floor area of the interior room or space, but not less than 25 square feet (2.33 m²). The ventilation openings to the outdoors shall be based on a total floor area being ventilated.

403.2 Bathrooms and toilet rooms. Every bathroom and toilet room shall comply with the ventilation requirements for habitable spaces as required by Section 403.1, except that a window shall not be required in such spaces equipped with a mechanical ventilation system. Air exhausted by a mechanical ventilation system from a bathroom or toilet room shall discharge to the outdoors and shall not be recirculated.

403.3 Cooking facilities. Unless approved through the certificate of occupancy, cooking shall not be permitted in any rooming unit or dormitory unit, and a cooking facility or appliance shall not be permitted to be present in a rooming unit or dormitory unit.

Exception: Where specifically approved in writing by the code official.

403.4 Process ventilation. Where injurious, toxic, irritating or noxious fumes, gases, dusts or mists are generated, a local exhaust ventilation system shall be provided to remove the contaminating agent at the source. Air shall be exhausted to the exterior and not be recirculated to any space.

403.5 Clothes dryer exhaust. Clothes dryer venting systems shall be independent of all other systems and shall be vented in accordance with the manufacturer's instructions.

SECTION 404 OCCUPANCY LIMITATIONS

404.1 Privacy. Dwelling units, hotel units, rooming units and dormitory units shall be arranged to provide privacy and be separate from other adjoining spaces.

404.2 Minimum room widths. A habitable room, other than a kitchen, shall not be less than 7 feet (2134 mm) in any plan dimension. Kitchens shall have a clear passageway of not less than 3 feet (914 mm) between counterfronts and appliances or counterfronts and walls.

404.3 Minimum ceiling heights. Habitable spaces, hallways, corridors, laundry areas, bathrooms, toilet rooms and habitable basement areas shall have a clear ceiling height of not less than 7 feet (2134 mm).

Exceptions:

1. In one- and two-family dwellings, beams or girders spaced not less than 4 feet (1219 mm) on center and projecting not more than 6 inches (152 mm) below the required ceiling height.
2. Basement rooms in one- and two-family dwellings occupied exclusively for laundry, study or recreation purposes, having a ceiling height of not less than 6 feet 8 inches (2033 mm) with not less than 6 feet 4 inches (1932 mm) of

clear height under beams, girders, ducts and similar obstructions.

3. Rooms occupied exclusively for sleeping, study or similar purposes and having a sloped ceiling over all or part of the room, with a clear ceiling height of at least 7 feet (2134 mm) over not less than one-third of the required minimum floor area. In calculating the floor area of such rooms, only those portions of the floor area with a clear ceiling height of 5 feet (1524 mm) or more shall be included.

404.4 Bedroom requirements. Every bedroom shall comply with the requirements of Sections 404.4.1 through 404.4.5.

404.4.1 Area for sleeping purposes. Every bedroom occupied by one person shall contain at least 70 square feet (6.5 m²) of floor area, and every bedroom occupied by more than one person shall contain at least 50 square feet (4.6 m²) of floor area for each occupant thereof.

404.4.2 Access from bedrooms. Bedrooms shall not constitute the only means of access to other bedrooms or habitable spaces and shall not serve as the only means of egress from other habitable spaces.

Exceptions:

1. Units that contain fewer than two bedrooms.
2. Existing residential occupancies as defined in Section 310.1 of the [BOCA National Building Code, 1999 edition](#).

404.4.4.3 Water closet accessibility. Every bedroom shall have access to at least one water closet and one lavatory without passing through another bedroom. Every bedroom in a dwelling unit shall have access to at least one water closet and lavatory located in the same story as the bedroom or an adjacent story.

Exception: Existing residential occupancies as defined in Section 310.1 of the [BOCA National Building Code, 1999 edition](#).

404.4.4 Prohibited occupancy. Kitchens and nonhabitable spaces shall not be used for sleeping purposes.

404.4.5 Other requirements. Bedrooms shall comply with the applicable provisions of this code including, but not limited to, the light, ventilation, room area, ceiling height and room width requirements of this chapter; the plumbing facilities and water-heating facilities requirements of Chapter 5; the heating facilities and electrical receptacle requirements of Chapter 6; and the smoke detector and emergency escape requirements of Chapter 7.

404.5 Overcrowding. Dwelling units shall not be occupied by more occupants than permitted by the minimum area requirements of Table 404.5.

**TABLE 404.5
MINIMUM AREA REQUIREMENTS**

SPACE	MINIMUM AREA IN SQUARE FEET		
	1-2 occupants	3-5 occupants	6 or more occupants
Living room ^{a,b}	No requirements	120	150
Dining room ^{a,b}	No requirements	80	100
Kitchen ^b	50	50	60
Bedrooms	Shall comply with section 404.4		

For SI: 1 square foot = 0.093 m².

^a See Section 404.5.2 for combined living room/dining room spaces.

^b See Section 404.5.1 for limitations on determining the minimum occupancy area for sleeping purposes.

404.5.1 Sleeping area. The minimum occupancy area required by Table 404.5 shall not be included as a sleeping area in determining the minimum occupancy area for sleeping purposes. All sleeping areas shall comply with Section 404.4.

404.5.2 Combined spaces. Combined living room and dining room spaces shall comply with the requirements of Table 404.5 if the total area is equal to that required for separate rooms and if the space is located so as to function as a combination living room/dining room.

404.6 Efficiency unit. Nothing in this section shall prohibit an efficiency living unit from meeting the following requirements:

1. A unit occupied by not more than two occupants shall have a clear floor area of not less than 220 square feet (20.4 m²). A unit occupied by three

occupants shall have a clear floor area of not less than 320 square feet (29.7 m²). These required areas shall be exclusive of the areas required by Items 2 and 3.

2. The unit shall be provided with a kitchen sink, cooking appliance and refrigeration facilities, each having a clear working space of not less than 30 inches (762 mm) in front. Light and ventilation conforming to this code shall be provided.
3. The unit shall be provided with a separate bathroom containing a water closet, lavatory, and bathtub or shower.
4. The maximum number of occupants shall be three.

404.7 Food preparation. All spaces to be occupied for food preparation purposes shall contain suitable space and equipment to store, prepare and serve foods in a sanitary manner. There shall be adequate facilities and services for the sanitary disposal of food wastes and refuse, including facilities for temporary storage.

CHAPTER 5 PLUMBING FACILITIES AND FIXTURE REQUIREMENTS

SECTION 501 GENERAL

501.1 Scope. The provisions of this chapter shall govern the minimum plumbing systems, facilities and plumbing fixtures to be provided.

501.2 Responsibility. The owner of the structure shall provide and maintain such plumbing facilities and plumbing fixtures in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any structure or premises which does not comply with the requirements of this chapter.

SECTION 502 REQUIRED FACILITIES

502.1 Dwelling units. Every dwelling unit shall contain its own bathtub or shower, lavatory, water closet and kitchen sink which shall be maintained in a sanitary, safe working condition. The lavatory shall be placed in the same room as the water closet or located in close proximity to the door leading directly into the room in which such water closet is located. A kitchen sink shall not be used as a substitute for the required lavatory.

502.2 Rooming houses. At least one water closet, lavatory and bathtub or shower shall be supplied for each four rooming units.

502.3 Hotels. Where private water closets, lavatories, and baths are not provided, one water closet, one lavatory and one bathtub or shower having access from a public hallway shall be provided for each ten occupants.

502.4 Employees' facilities. A minimum of one water closet, one lavatory and one drinking facility shall be available to employees.

502.4.1 Drinking facilities. Drinking facilities shall be a drinking fountain, water cooler, bottled water cooler, or disposable cups next to a sink or water dispenser. Drinking facilities shall not be located in toilet rooms or bathrooms.

SECTION 503 TOILET ROOMS

503.1 Privacy. Toilet rooms and bathrooms shall provide privacy and shall not constitute the only passageway to a hall or other space, or to the exterior. A door and interior locking device shall be provided for all common or shared bathrooms and toilet rooms in a multiple dwelling.

503.2 Location. Toilet rooms and bathrooms serving hotel units, rooming units or dormitory units, shall have access by traversing not more than one flight of stairs and shall have access from a common hall or passageway.

503.3 Location of employee toilet facilities. Toilet facilities shall have access from within the employees' regular working area. The required toilet facilities shall be located not more than one story above or below the employees' regular working area and the path of travel to such facilities shall not exceed a distance of 500 feet (152 m). Employee facilities shall either be separate facilities or public customer facilities.

Exception: Facilities that are required for employees in storage structures or kiosks, which are located in adjacent structures under the same ownership, lease or control, shall not exceed a travel distance of 500 feet (152 m) from the employees' regular working area to the facilities.

SECTION 504 PLUMBING SYSTEMS AND FIXTURES

504.1 General. All plumbing fixtures shall be properly installed and maintained in working order, and shall be kept free from obstructions, leaks and defects and be capable of performing the function for which such plumbing fixtures are designed. All plumbing fixtures shall be maintained in a safe, sanitary and functional condition.

504.2 Fixture clearances. Plumbing fixtures shall have adequate clearances for usage and cleaning.

504.3 Plumbing system hazards. Where it is found that a plumbing system in a structure constitutes a hazard to the occupants or the structure by reason of inadequate service, inadequate venting, cross connection, backsiphonage, improper installation, deterioration or damage or for similar reasons, the code official shall require the defects to be corrected to eliminate the hazard.

SECTION 505 WATER SYSTEM

505.1 General. Every sink, lavatory, bathtub or shower, drinking fountain, water closet or other plumbing fixture shall be properly connected to either a public water system or to an approved private water system. All kitchen sinks, lavatories, laundry facilities, bathtubs and showers shall be supplied with hot or tempered and cold running water in accordance with the plumbing code.

505.2 Contamination. The water supply shall be maintained free from contamination, and all water inlets for plumbing fixtures shall be located above the flood-level rim of the fixture. Shampoo basin faucets, janitor sink faucets, and other hose bibs or faucets to which hoses are attached and left in place, shall be protected by an approved atmospheric-type vacuum breaker or an approved permanently attached hose connection vacuum breaker.

505.3 Supply. The water supply system shall be installed and maintained to provide a supply of water to plumbing fixtures, devices and appurtenances in sufficient volume and at pressures adequate to enable the fixtures to function properly, safely, and free from defects and leaks.

505.4 Water heating facilities. Water heating facilities shall be properly installed, maintained and capable of providing an adequate amount of water to be drawn at every required sink, lavatory, bathtub, shower and laundry facility at a temperature of not less than 120°F. (49°C.). A gas-burning water heater shall not be located in any bathroom, toilet room, bedroom or other occupied room normally kept closed, unless adequate combustion air is provided. An approved combination temperature and pressure relief valve and relief valve discharge pipe shall be properly installed and maintained on water heaters.

SECTION 506 SANITARY DRAINAGE SYSTEM

506.1 General. All plumbing fixtures shall be properly connected to a public sewer system.

506.2 Maintenance. Every plumbing stack, vent, waste and sewer line shall function properly and be kept free from obstructions, leaks and defects.

506.3 Cesspools. No person shall construct or place or cause to be constructed or placed on any premise or property any cesspool, privy, vault, dump, or pit of like purpose, nor allow or cause any plumbing fixtures to be connected to such.

SECTION 507 STORM DRAINAGE

507.1 General. Drainage of roofs and paved areas, yards and courts, and other open areas on the premises shall not be discharged in a manner that creates a public nuisance.

CHAPTER 6 MECHANICAL AND ELECTRICAL REQUIREMENTS

SECTION 601 GENERAL

601.1 Scope. The provisions of this chapter shall govern the minimum mechanical and electrical facilities and equipment to be provided.

601.2 Responsibility. The owner of the structure shall provide and maintain mechanical and electrical facilities and equipment in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any premises which does not comply with the requirements of this chapter.

SECTION 602 HEATING FACILITIES

602.1 Facilities required. Heating facilities shall be provided in structures as required by this section.

602.2 Residential occupancies. Dwellings shall be provided with heating facilities capable of maintaining a room temperature of 65°F (18°C.) in all habitable rooms, bathrooms and toilet rooms based on the winter outdoor design temperature for the locality indicated in Appendix D of the plumbing code.

602.3 Heat supply. Every owner and operator of any building who rents, leases or lets one or more dwelling unit, rooming unit, dormitory or guestroom on terms expressed or implied, to furnish heat to the occupants thereof shall supply heat during the period from **October 1 to April 30** inclusive to maintain a temperature of not less than 65°F (18°C) in all habitable rooms, bathrooms, and toilet rooms.

Exception: When the outdoor temperature is below the winter outdoor design temperature for the locality, maintenance of the minimum room temperature shall not be required provided that the heating system is operating at its full design capacity. The winter outdoor design temperature for the locality shall be as indicated in Appendix D of the plumbing code.

602.4 Occupiable work spaces. Indoor occupiable

work Spaces shall be supplied with heat during the period from October 1 to April 30 inclusive to maintain a temperature of not less than 65°F (18°C) during the period the spaces are occupied.

Exceptions:

1. Processing, storage and operation areas that require cooling or special temperature conditions.
2. Areas in which persons are primarily engaged in vigorous physical activities.

602.5 Room temperature measurement. The required room temperatures shall be measured 3 feet (914 mm) above the floor near the center of the room and 2 feet (610 mm) inward from the center of each exterior wall.

SECTION 603 MECHANICAL EQUIPMENT

603.1 Mechanical equipment. All mechanical equipment, fireplaces and solid fuel-burning appliances shall be properly installed and maintained in a safe working condition, and shall be capable of performing the intended function.

603.2 Cooking and heating equipment. All cooking and heating equipment, components and accessories in every heating, cooking and water-heating device shall be maintained free from leaks and obstructions.

603.2.1 Cooking equipment. Cooking appliances shall not be used to provide space heating to meet the minimum requirements of Section 602.3.

603.3 Removal of combustion products. All fuel-burning equipment and appliances shall be connected to an approved chimney or vent.

Exception: Fuel-burning equipment and appliances which are labeled for unvented operation.

603.4 Clearances. All required clearances to combustible materials shall be maintained.

603.5 Safety controls. All safety controls for fuel-burning equipment shall be maintained in effective operation.

603.6 Combustion air. A supply of air for complete combustion of the fuel and for ventilation of the space containing the fuel-burning equipment shall be provided for the fuel-burning equipment.

603.7 Energy conservation devices. Devices intended to reduce fuel consumption by attachment to a fuel-burning appliance, to the fuel supply line thereto, or to the vent outlet or vent piping therefrom, shall not be installed unless labeled for such purpose and the installation is specifically approved.

SECTION 604 ELECTRICAL FACILITIES

604.1 Facilities required. Every occupied building shall be provided with an electrical system in compliance with the requirements of this section and Section 605.

604.2 Service. The size and usage of appliances and equipment shall serve as a basis for determining the need for additional facilities in accordance with NFPA 70. Every dwelling shall be served by a main service that is not less than 60 amperes, three wires.

604.3 Electrical system hazards. Where it is found that the electrical system in a structure constitutes a hazard to the occupants or the structure by reason of inadequate service, improper fusing, insufficient outlets, improper wiring or installation, deterioration or damage, or for similar reasons, the code official shall require the defects to be corrected to eliminate the hazard.

SECTION 605 ELECTRICAL EQUIPMENT

605.1 Installation. All electrical equipment, wiring and appliances shall be properly installed and maintained in a safe and approved manner.

605.2 Receptacles. Every habitable space in a dwelling shall contain at least two separate and remote receptacle outlets. Every laundry area shall contain at least one grounded-type receptacle or a receptacle with a ground fault circuit interrupter. Every bathroom shall contain at least one receptacle. Any new bathroom

receptacle outlet shall have ground fault circuit interrupter protection.

605.3 Lighting fixtures. Every public hall, interior stairway, toilet room, kitchen, bathroom, laundry room, boiler room and furnace room shall contain at least one electric lighting fixture.

SECTION 606 ELEVATORS, ESCALATORS AND DUMBWAITERS

606.1 General. Elevators, dumbwaiters and escalators shall be maintained to sustain safely all imposed loads, to operate properly, and to be free from physical and fire hazards. The most current certificate of inspection shall be on display at all times within the elevator or attached to the escalator or dumbwaiter; or the certificate shall be available for public inspection in the office of the building operator.

606.2 Elevators. In buildings equipped with passenger elevators, at least one elevator shall be maintained in operation at all times when the building is occupied.

Exception: Buildings equipped with only one elevator shall be permitted to have the elevator temporarily out of service for testing or servicing.

SECTION 607 DUCT SYSTEMS

607.1 General. Duct systems shall be maintained free of all obstructions and shall be capable of providing the required function.

CHAPTER 7
FIRE SAFETY REQUIREMENTS

**SECTION 701
GENERAL**

701.1 Scope. The provisions of this chapter shall govern the minimum conditions and standards for fire safety relating to structures and exterior premises, including fire safety facilities and equipment to be provided.

701.2 Responsibility. The owner of the premises shall provide and maintain such fire safety facilities and equipment in compliance with these requirements. A person shall not occupy as owner-occupant or permit another person to occupy any premises that do not comply with the requirements of this chapter.

**SECTION 702
MEANS OF EGRESS**

702.1 General. A safe, continuous and unobstructed path of travel shall be provided from any point in a building or structure to the public way.

702.2 Exit capacity. The capacity of the exits serving a floor shall be sufficient for the occupant load thereof as determined by the building code.

702.3 Number of exits. In nonresidential buildings, every occupied story more than six stories above grade shall be provided with not less than two independent exits. In residential buildings, every story exceeding two stories above grade shall be provided with not less than two independent exits. In stories where more than one exit is required, all occupants shall have access to at least two exits. Every occupied story which is both totally below grade and greater than 2,000 square feet (186 m²) shall be provided with not less than two independent exits.

Exception: A single exit is acceptable under any one of the following conditions:

1. Where the building is equipped throughout with an automatic sprinkler system and an automatic fire detection system with smoke detectors located in all corridors, lobbies and common areas.
2. Where the building is equipped throughout

with an automatic fire detection system and the exit is an approved smokeproof enclosure or pressurized stairway.

3. Where an existing fire escape conforming to the building code is provided in addition to the single exit.
4. Where permitted by the building code.
5. Use groups R-2, R-3 and R-4 which, existing on the effective date of this ordinance and are equipped with properly installed and maintained single or multiple station smoke alarms.

702.4 Arrangement. Exits from dwelling units, rooming units, guestrooms and dormitory units shall not lead through other such units, or through toilet rooms or bathrooms.

702.5 Exit signs. All means of egress shall be indicated with approved "Exit" signs where required by the building code. All "Exit" signs shall be maintained visible and all illuminated "Exit" signs shall be illuminated at all times that the building is occupied.

702.6 Corridor enclosure. All corridors serving an occupant load greater than 30 and the openings therein shall provide an effective barrier to resist the movement of smoke. All transoms, louvers, doors and other openings shall be closed or shall be self-closing.

Exceptions:

1. Corridors in occupancies, other than high-hazard occupancies, which are equipped throughout with an automatic sprinkler system.
2. Patient room doors in corridors in health care occupancies where smoke barriers are provided in accordance with the fire prevention code, are not required to be self-closing.
3. Corridors in educational occupancies where each room that is occupied for instruction or assembly purposes has at least one-half of the required means of egress doors opening directly to the exterior of the building at ground level.

4. Corridors that are in compliance with the building code.

702.7 Dead-end travel distance. All corridors that serve more than one exit shall provide direct connection to such exits. The length of a dead-end corridor shall not exceed 35 feet (10668 mm) where the building is not equipped throughout with an automatic sprinkler system. The dead-end travel distance limitation shall be increased to 70 feet (21336 mm) where the building is equipped throughout with an automatic sprinkler system.

Exception: Dead ends that are in compliance with the building code.

702.8 Aisles. Arrangements of chairs or tables and chairs shall provide for ready access by aisle accessways and aisles to each egress door. The minimum clear width of each aisle in assembly, educational and health care occupancies shall be maintained in accordance with the requirements of the building code. In all other occupancies, aisles shall have a minimum required clear width of 44 inches (1118 mm) where serving an occupant load greater than 50, and 36 inches (914 mm) where serving an occupant load of 50 or less. The clear width of aisles shall not be obstructed by chairs, tables or other objects.

702.9 Stairways, handrails and guards. Every exterior and interior flight of means of egress stairs serving any building or portion thereof and having more than four risers shall have a handrail on at least one side of the stair. Every open portion of a stair, landing, balcony, porch, deck, ramp or other walking surface which is more than 30 inches (762 mm) above the floor or, grade below shall have guards. Handrails shall not be less than 30 inches (762 mm) nor more than 42 inches (1067 mm) high, measured vertically above the nosing of the tread or above the finished floor of the landing or walking surface. Guards shall not be less than 30 inches (762 mm) high above the floor of the landing, balcony, porch, deck, ramp or other walking surface.

Exception: Guards are not required at any location where guards are exempted by the building code.

702.10 Stairway identification. A sign shall be provided at each floor landing in all interior stairways more than three stories above grade, designating the floor level above the floor of exit discharge. All elevator lobby call stations on all floor levels shall be identified

by approved signs in accordance with the requirements for new buildings in the building code.

Exception: The emergency sign shall not be required for elevators that are part of an accessible means of egress complying with the building code.

702.11 Locked doors. All means of egress doors shall be readily openable from the side from which egress is to be made without the need for keys, special knowledge or effort, except as provided for in Section 702.11.1.

702.11.1 Locks permitted. Locks or fasteners shall not be installed on egress doors except in accordance with the following conditions:

1. In mental, penal or other institutions where the security of inmates is necessary, in which case properly trained supervisory personnel shall be continuously on duty and approved provisions are made to remove occupants safely in case of fire or other emergency.
2. In problem security areas, special-purpose door alarms or locking devices shall be approved prior to installation. Manually operated edge or surfacemolded flush bolts are prohibited.
3. Where the door hardware conforms to that permitted by the building code.

702.12 Emergency escape. Every sleeping room located below the third story in residential and group home occupancies shall have at least one openable window or exterior door approved for emergency egress or rescue; or shall have access to not less than two approved independent exits.

Exception: Buildings equipped throughout with an automatic fire suppression system.

702.12.1 Security. Bars, grilles or screens placed over emergency escape windows shall be releasable or removable from the inside without the use of a key, tool or force greater than that which is required for normal operation of the window.

SECTION 703 ACCUMULATIONS AND STORAGE

703.1 Accumulations. Rubbish, garbage or other

materials shall not be stored or allowed to accumulate in stairways, passageways, doors, windows, fire escapes or other means of egress.

703.2 Hazardous material. Combustible, flammable, explosive or other hazardous materials, such as paints, volatile oils and cleaning fluids, or combustible rubbish, such as wastepaper, boxes and rags, shall not be accumulated or stored unless such storage complies with the applicable requirements of the building code and the fire prevention code.

SECTION 704 FIRE RESISTANCE RATINGS

704.1 General. The fire resistance rating of floors, walls, ceilings, and other elements and components required by the building code shall be maintained.

704.2 Maintenance. All required fire doors and smoke barriers shall be maintained in good working order, including all hardware necessary for the proper operation thereof. Fire doors shall not be held open by door stops, wedges and other unapproved hold-open devices.

SECTION 705 FIRE PROTECTION SYSTEMS

705.1 General. All systems, devices and equipment to detect a fire, actuate an alarm, or suppress or control a fire or any combination thereof shall be maintained in an operable condition at all times in accordance with the fire prevention code.

705.2 Fire suppression system. Fire suppression systems shall be maintained in proper operating condition at all times.

705.3 Standpipe systems. Standpipe systems shall be maintained in proper operating condition at all times. Hose connections shall be unobstructed.

705.4 Fire extinguishers. All portable fire extinguishers shall be visible, provided with ready access thereto, and maintained in an efficient and safe operating condition. Extinguishers shall be of an approved type.

705.5 Smoke detectors. A minimum of one approved single-station or multiple-station smoke detector shall be installed in each guestroom, suite or sleeping area in residential and group home occupancies, and in dwelling units in the immediate vicinity of the bedrooms in occupancies in one- and two-family dwellings and multifamily dwellings. In all residential occupancies, smoke detectors shall be required on every story of the dwelling unit, including basements. In dwelling units with split levels and without an intervening door between the adjacent levels, a smoke detector installed on the upper level shall suffice for the adjacent lower level, provided that the lower level is less than one full story below the upper level.

705.5.1 Installation. All detectors shall be installed in accordance with the building code and the manufacturer's instructions. When actuated, the smoke detectors shall provide an alarm suitable to warn the occupants within the individual room or dwelling unit.

705.5.2 Power source. The power source for smoke detectors shall be either an AC primary power source or a monitored battery primary power source.

705.5.3 Tampering. Anyone tampering or interfering with the effectiveness of a smoke detector shall be in violation of this code.

705.5.4 Tests and Maintenance. All single and multiple station smoke alarms shall be tested in accordance with the [BOCA National Fire Prevention Code](#), as is otherwise adopted by the Village of Ashville, Ohio.

705.6 Fire alarm systems. Fire alarm systems shall be in proper operating condition at all times.

CHAPTER 8 REFERENCED STANDARDS

This chapter lists the standards that are referenced in various sections of this document. The standards are listed here in by the promulgating agency of the standard, the standard identification, the effective date and title, and the section or sections of this document that reference the standard. The application of the referenced standards shall be as specified in Section 102.8.

ASME

American Society of Mechanical Engineers
345 East 47th Street
New York, NY 10017-2392

Standard Reference Number	Title	Referenced in code section number
A17.1-93	Safety Code for Elevators and Escalators - with A17.la-94 Addendum	201.3

CODES

Standard Reference Number	Title	Referenced in code section number
Building Code	BOCA National Building Code, 1999 edition as is otherwise adopted by the Village of Ashville, Ohio	102.3, 201.3, 302.7.1, 401.3, 702.2, 702.3, 702.5, 702.6, 702.7, 702.8, 702.9, 702.10, 702.11.1, 703.2, 704.1, 705.5.1
Fire Prevention Code	BOCA National Fire Prevention Code, 1999 edition as is otherwise adopted by the Village of Ashville, Ohio	201.3, 702.6, 703.2, 705.1
Mechanical Code	BOCA National Mechanical Code, 1996 edition as is otherwise adopted by the Village of Ashville, Ohio	102.3, 201.3
IPC-97		
IZC-98	ICC International Plumbing Code - with 1998 Supplement	102.3, 201.3, 505.1, 602.2, 602.3
	ICC International Zoning Code	102.3, 201.3

NFPA

National Fire Protection Association
Batterymarch Park
Quincy, MA 02269

Standard Reference number	Title	Referenced in code section number
70-96	National Electrical Code	102.3, 201.3, 604.2

INDEX

A

ACCEPTED ENGINEERING METHODS	104.2
ACCESS	
Egress	702
Fire extinguishers	705.4
From bedrooms	404.4.2
Plumbing fixtures, access for cleaning.....	504.2
Standpipes	705.3
To public way	702.1
Toilet room as passageway	503.1
Water closet	404.4.3
ADJACENT	
Privacy (hotel units, rooming units).....	404.1
ADMINISTRATION	
Scope	101.2
Severability	101.4
AGENT (See OPERATOR)	
AIR	
Combustion air	603.6
AISLES	
Minimum width	702.8
ALTERATION	
Applicability of other codes	102.3
Condemnation	108.1, 108.2
Inspection	104.3
Prosecution	106.3
Unlawful acts	106.1
ANCHOR	
Architectural trim	303.8
Signs, marquees and awnings.....	303.9
APPEAL	
Application.....	111.1
Construction Board of	
Adjustment and Appeals	Appendix
Basis for appeal.....	A-190.8
Board decision.....	A-190.12
Compensation	A-190.13
Court review	A-190.12
Financial interest	A-190.3
Hearing.....	A-190.6
Membership	A-190.3
Notice of appeal	A-190.10
Postponed hearing	A-111.5
Records.....	A-190.5
Right to appeal	A-190.7
Saving clause	A-190.15
Severability	A-190.16
Vote.....	A-190.4
APPLIANCE	
Cooking.....	603.2.1
APPLICATION	
Historic buildings	102.6

Other codes	102.3
APPROVAL	
Alternatives	105.2
Authority	104.1, 105.2
Modifications.....	105.1
APPROVED	
Alternative materials, methods and	
equipment.....	105.2
Cooking and heating equipment.....	603.2
Definition.....	202
Energy conservation devices	603.7
Fireplaces	603.1
Garbage storage facilities	305.3.1
Hazardous materials storage	703.2
Modifications.....	105.1
Used materials and equipment	105.4
ARCHITECTURAL	
Structural members.....	303.4
Trim	303.8
ARTIFICIAL	
Lighting of habitable rooms	401.3
Lighting of other spaces	402.3
AUTOMOBILE	
Motor vehicles.....	302.8
AWNING	
Signs, marquees and awnings	303.9

B

BALCONY	
Handrails and guardrails	303.10, 303.13, 702.9
Maintenance	303.11
BASEMENT	
Definition.....	202
Hatchways	303.17
Windows	303.18
BATHROOM	
Common bathrooms	502.3, 503.1
Hotels	502.3
Lighting	605.3
Locks	503.1
Outlets required	605.2
Privacy.....	503.1
Ventilation	403.2
BATHTUB	
Required facilities	502.1
Rooming houses	502.2
Sewage system	506.1
Water heating facilities	505.4
Water system.....	505.1
BOILER	
Unsafe equipment.....	108.1.2

C

CAPACITY

Heating facilities 602.2, 602.3, 602.4

CAR (See AUTOMOBILE)

CEILING

Basement rooms.....404.3
Fire-resistance ratings 704.1
Interior surfaces 304.3
Minimum height 404.3

CHANGE, MODIFY

Application of other codes..... 102.3

CHIMNEY

Exterior structure303.12
Fireplaces603.1
Flue, Connected to.....603.3

CLEANING

Access for cleaning.....504.2
Bathroom and kitchen floors 304.3
Disposal of garbage.....305.3
Disposal of rubbish305.2
Interior sanitation 305.1
Interior surfaces 304.3
Occupant 304.1
Plumbing facilities, maintained 504.1
Required plumbing facilities 502
Responsibility of persons 304.1
Trash containers305.3.2
Vacant structures and land 301.3

CLEARANCE

Mechanical Equipment.....603.4
Plumbing fixtures504.2

CLOSING

Streets 109.3
Vacant structures.....108.2

CLOTHES DRYER

Exhaust.....403.5

CODE OFFICIAL

Condemnation 108.1
Coordination of enforcement..... 104.8
Demolition..... 110
Deputies 103.3
Duties 104
Emergency measures 109
Enforcement authority..... 104.1
Enforcement powers 104.9
Failure to comply with demolition order 110.3
Identification..... 104.5
Inspections 104.3
Liability, relief of personal..... 103.5
Membership of board of appeals..... A-190.3
Notice of violation 104.6, 107
Notices and orders..... 107
Official records..... 104.7
Personal liability..... 103.5
Placarding..... 108.4

Prosecution 106.3
Removal of placard 108.6
Restriction of employees 103.3
Right of entry..... 104.4
Rule-making authority 104.2
Transfer of ownership..... 107.5
Vacant structures 108.2
Voting of appeals board..... A-190.4

COLD WATER

Drinking 502.4
Required facilities 502
Rooming houses 502.2
Water system 505

COMBUSTIBLE

Storage 703.2

COMBUSTION

Combustion air 603.6

CONDEMNATION

Closing of vacant structures 108.2
Failure to comply 110.3
General 108.1
Notices and orders 108.2, 108.3
Placarding 108.4
Removal of placard 108.6

CONFLICT

Conflict of interest.....A-190.3
Coordination of inspections 104.8
Violations..... 106.1

CONNECTION

Plumbing fixtures..... 504.1
Sewage system..... 506.1
Water heating..... 505.4
Water system 505.1

CONSTRUCTION

Existing structures 101.2

CONTAINER

Garbage 305.3.2
Rubbish storage 305.2.1

CONTINUOUS

Egress..... 702.1

CONTRACTOR

Conflict of interest.....A-190.3

CONTROL

Insect and rodent control 302.5, 303.5, 306.1
Safety controls 603.5

COOLING

Cooling towers 303.12

CORRIDOR

Accumulation of rubbish 305.1
Enclosure 702.6, 704
Light 402.2
Lighting fixtures 605.3
Toilet rooms, access 503.1

D

DAMP, DAMPNES

- Roofs 303.7
- Window, door frames 303.14

DANGEROUS, HAZARDOUS

- Condemnation 108.1
- Demolition 110
- Electrical hazards 604.3
- Elevators 606.1
- Existing remedies 102.4
- Fire safety 701.1
- Heating facilities 603.2
- Sidewalks and driveways 302.3
- Unsafe structures and equipment 108

DECORATION

- Exterior structure 303.8

DEMOLITION

- Existing remedies 102.4
- Failure to comply 110.3
- General 110.1
- Order 110.2
- Salvage materials 110.4
- Violations 110.3

DETECTORS

- Fire alarms 705.1
- Installation 705.5.1
- Power 705.5.2
- Smoke 705.5

DETERIORATION

- Exterior walls 303.6

DIRECT

- Egress 702.1

DISPOSAL

- Disposal of garbage 305.3
- Disposal of rubbish 305.2

DOOR

- Exit doors 702.11
- Fire 704.2
- Hardware 303.16
- Insect screens 303.15
- Interior surfaces 304.3
- Locks 303.16, 702.11
- Maintenance 303.14, 303.16, 704.2
- Weather tight 303.14
- Window and door frames 303.14

DORMITORY (ROOMING HOUSE, HOTEL, MOTEL)

- Locked doors 702.11
- Privacy 503.1, 503.2
- Storage 703.2

DRAIN, DRAINAGE

- Basement hatchways 303.17
- Grading 302.2
- Plumbing connections 506
- Storm drainage 507

DUCT

- Exhaust duct 303.9

DUST

- Process ventilation 403.4

DWELLING

- Cleanliness 304.1, 305.1
- Definition 202
- Electrical 604.1
- Heating facilities 602
- Required facilities 502
- Space requirements 404.5

E

EGRESS

- Aisles 702.8
- Arrangement 702.4
- Capacity 702.2
- Common halls and stairways 402.2
- Corridors 702.6
- Dead ends 702.7
- Emergency escape 702.12
- Exit facilities maintained
and provided 304.4, 304.5, 702.9
- Exit signs 702.5
- Fire escapes 702.3
- General 702.1
- Information signs 702.10
- Locked doors 702.11
- Number of exits 702.3
- Signs 702.5
- Stairs, porches
and railings 303.11, 304.5, 702.9
- Waste accumulation 703.1

ELECTRIC, ELECTRICAL

- Condemnation 108.1
- Facilities required 604.1
- General 601
- Hazards 604.3
- Installation 605.1
- Lighting fixtures 605.3
- Receptacles 605.2
- Responsibility 601.2
- Service 604.2

ELEVATOR

- Condemnation 108.1
- General 606.1
- Maintenance 606.1, 606.2
- Signs 702.10

EMERGENCY

- Costs of emergency repairs 109.5
- Emergency measures 109
- Emergency orders 109.1
- Emergency repairs 109.4
- Escape 702.12

ENFORCEMENT

- Coordination 104.8

Duties and powers	104
Scope	101.2
EQUIPMENT	
Alternative	105.2
Combustion air	603.6
Condemnation	108.1.2, 108.3
Cooking and heating	603.2
Electrical installation	605.1
Emergency order	109.1
Energy conservation devices	603.7
Fire-protection systems.....	705.1
Fire safety requirements, responsibility	
701.2	
Flue	603.3
Installation	603.1
Interior structure.....	304.1
Placarding.....	108.3, 108.4
Prohibited use.....	108.5
Responsibility.....	601.2
Safety controls	603.5
Scope	101.2
Scope, mechanical and electrical.....	601.1
Unsafe	108
Used	105.4
EXCEPTION	
Rule-making authority	104.2
EXHAUST	
Clothes dryer	403.5
Exhaust ducts	303.9
Process ventilation.....	403.4
EXISTING	
Historic buildings.....	102.6
Remedies	102.4
Scope	101.2
Structural members.....	303.4
Structures	101.3
EXTERIOR	
Decorative features.....	303.8
Egress	702.1
Exterior structure	303
Exterior walls	303.6
Painting.....	303.2, 303.6
Rodent harborage.....	302.5, 303.5
Sanitation.....	303.1
Scope	301.1
Stair	303.10, 303.11
Street numbers	303.3
Weather tight	303.14
EXTERMINATE	
Definition.....	202
Insect and rodent control... 302.5, 303.15, 306.1	
Responsibility of owner	306.2
Responsibility of tenant-occupant	306.5

	F
FAN	
Exhaust vents.....	302.6
FEES, EXPENSES, COST	
Closing vacant structures	108.2
Demolition	110.1, 110.3, 110.4
Extermination	306.2, 306.3, 306.4, 306.5
General	103.6
Relief from personal liability.....	103.5
Responsibility, fire safety.....	701.2
FENCE	
Accessory.....	302.7
FIRE	
Fire escapes.....	702.3
Fire extinguishers.....	705.4
Fire-suppression system	705.2
Fire-resistance ratings.....	704.1
General, fire-protection systems.....	705
Protection systems	705
Responsibility, fire safety	701.2
Scope.....	101.2
Scope, fire safety.....	701.1
Signaling systems	705.6
Smoke detectors	705.5
Standpipe system.....	705.3
FLAMMABLE LIQUID	
Containers.....	108.1.2
Flammable matter	703.2
FLOOR, FLOORING	
Area for sleeping purposes.....	404.5.1
Fire-resistance ratings.....	704.1
Interior surfaces.....	304.1, 304.3
Space requirements	404.5, 404.6
FOOD PREPARATION	
Cooking equipment	403.3, 603.2
Sanitary condition.....	304.1, 404.7
Ventilation	403.4
FOUNDATION	
Condemnation.....	108.1.1
Foundation walls	303.5
FRAME	
Window and door frames.....	303.14
	G
GAS	
Energy conservation devices.....	603.7
Exhaust vents.....	302.6
Process ventilation	403.4
GLAZING	
Materials	303.14.1
GRADE	
Drainage	302.2
GUARD	
Basement windows	303.18
Handrails.....	303.13

H

HABITABLE
 Definition..... 202
 Light..... 402
 Minimum ceiling height 404.3
 Minimum room width..... 404.2
 Nonresidential heating facilities..... 602.4
 Prohibited use..... 404.4.4
 Required plumbing facilities 502
 Residential heating facilities 602.2, 602.3
 Space requirements..... 404.5
 Ventilation 403

HANDRAIL
 Handrails 303.13, 304.6, 702.9
 Stairs and porches..... 303.11

HARDWARE
 Door hardware 303.16, 702.11
 Openable windows..... 303.14.2

HAZARDOUS (See DANGEROUS, HAZARDOUS)

HEAT, HEATING
 Bathtub or shower..... 505.4
 Cooking and heating equipment..... 603.2
 Energy conservation devices 603.7
 Fireplaces 603.1
 Kitchen sink 505.4
 Mechanical equipment..... 603.1
 Required capabilities..... 602
 Residential heating 602.2, 602.3
 Scope 101.2
 Supply..... 602.3
 Water closet and lavatory..... 505.4
 Water heating 505.4
 Water system..... 505

HEIGHT
 Minimum ceiling height 404.3

HOT (See HEAT, HEATING)

HOTELS, ROOMING HOUSES AND DORMITORY UNITS, MOTELS
 Definition..... 202
 Locked doors 702.11
 Privacy..... 503.1
 Toilet rooms 503

IDENTIFICATION
 Code official 104.5

INFESTATION
 Condemnation 108.1.3
 Definition..... 202
 Insect and rodent 302.5, 303.15, 306.1

INSECTS
 Extermination..... 306
 Garbage storage facilities 305.3
 Infestation 306.1
 Insect screens..... 303.15

INSPECTIONS
 Coordination 104.8

General 104.3
 Right of entry 104.4

INSPECTOR
 Coordination of inspections 104.8
 Identification 104.5
 Inspections 104.3
 Official records 104.7

INTENT
 Code 101.3
 Rule-making authority 104.2

INTERIOR
 Interior structure 304
 Interior surfaces..... 304.3
 Means of egress..... 702
 Sanitation 304.1

J

JURISDICTION
 Title 101.1

K

KITCHEN
 Electrical outlets required 605.2
 Floors 304.3
 Kitchen sink..... 502.1
 Minimum area Table 404.5
 Minimum width 404.2
 Prohibited use 404.4.4
 Water heating facilities 505.4

L

LANDING
 Handrails and guards 303.13, 304.6, 702.9

LAUNDRY
 Room lighting 605.3
 Water heating facilities 505.4

LAVATORY
 Hotels..... 502.3
 Required facilities 502
 Rooming houses 502.2
 Sewage system..... 506
 Water heating facilities 505.4
 Water system 505

LEASE (SELL, RENT)
 Heat supplied 602.3
 Salvage materials..... 110.4
 Transfer of ownership..... 107.5

LIEN
 Closing of vacant structures 108.2
 Demolition 110.3
 Failure to comply 110.3

LIGHT, LIGHTING
 Common halls and stairways..... 402.2, 605.3
 Exit signs..... 702.5
 Fixtures 605.3

General.....	401
Habitable rooms.....	402.1
Other spaces	402.3
Responsibility.....	401.2
Scope	101.2
Spaces or rooms.....	402.1
Toilet rooms	605.3

LIVING ROOM

Minimum occupancy area requirements....	404.5
---	-------

LOAD, LOADING

Elevators, escalators and dumbwaiters	606.1
Handrails	303.13
Live load	303.4, 304.2
Stairs and porches.....	303.11, 304.2
Structural members.....	303.4, 304.2

M

MAINTENANCE

Required.....	102.2
---------------	-------

MATERIAL

Alternative.....	105.2
Clearances, heating facilities	603.4
Salvage.....	110.4
Used	105.4

MEANS OF EGRESS (See EGRESS)

MECHANICAL

Garbage facilities	305.3.1
Installation	603.1
Responsibility.....	601.2
Scope	601.1
Ventilation, general.....	403
Ventilation, toilet rooms.....	403.2

MINIMUM

Ceiling height.....	404.3
Number of exits.....	702.3
Occupancy area requirements	404.5
Room width.....	404.2
Scope . 101.2, 301.1, 401.1, 501.1, 601.1, 701.1	

MODIFICATION

Approval	105.1
----------------	-------

MOTEL (See HOTELS)

N

NATURAL

Lighting.....	401.3, 402
Ventilation.....	401.3, 403

NOTICE

Appeal	A-190.10
Form	107.2
Method of service	107.3
Orders.....	107
Owner, responsible person	107.1
Penalties.....	107.4

Placarding of structure.....	108.4
Transfer of ownership.....	107.5
Vacating structure	108.2

NOXIOUS

Process ventilation	403.4
Weeds.....	302.4

NUISANCE

Closing of vacant structures	108.2
------------------------------------	-------

O

OBSTRUCTION

Light	402.1
Right of entry.....	104.4

OCCUPANCY (See USE)

OCCUPIED

Unlawful structure.....	108.1.4
-------------------------	---------

OPEN

Habitable rooms	403.1
Locked doors.....	702.11

OPENABLE

Definition	202
Locked doors.....	702.11
Windows	303.14.2

OPERATOR

Definition	202
------------------	-----

ORDER (See NOTICE)

ORDINANCE, RULE

Applicability	102
Application for appeal.....	A-190.7

OUTLET

Electrical	605.2
------------------	-------

OWNER

Closing of vacant structures	108.2
Definition	202
Demolition	110
Extermination	306.2
Failure to comply.....	110.3
Insect and rodent control	302.5, 306.2, 306.4
Notice.....	107.1, 108.3
Placarding of structure.....	108.4
Responsibility	301.2
Responsibility, fire safety.....	701.2
Responsibility, light, ventilation.....	401.2
Responsibility, mechanical and electrical	601.2
Responsibility, plumbing facilities	501.2
Right of entry.....	104.4
Rubbish storage	305.2.1
Scope.....	101.2
Transfer of ownership.....	107.5

P

PASSAGEWAY

Accumulations and storage	703.1
Common hall and stairway	402.2
Interior surfaces.....	304.3

Toilet rooms, direct access	503.1
PENALTY	
Notices and orders.....	107.4
Placarding of structure	108.4
Prohibited use.....	108.5
Removal of placard.....	108.6
Scope	101.2
Violations	106.4
PEST (VERMIN)	
Condemnation	108.1
Extermination.....	306.1
Insect and rodent control... 302.5, 303.15, 306.1	
PLACARD, POST	
Closing.....	108.2
Condemnation	108.1
Demolition.....	110
Emergency, notice	109.1
Notice to owner	107.1, 108.3
Placarding of structure	108.4
Prohibited use.....	108.5
Removal	108.6
PLUMBING	
Access.....	504.2
Clean and sanitary.....	504.1
Connections.....	505.1, 506.1
Contamination.....	505.2
Employee's facilities.....	503.3
Fixtures.....	504.1
Required facilities	502
Responsibility.....	501.2
Sanitary drainage system.....	506
Scope	501.1
Storm drainage	507
Supply.....	505.3
PORCH	
Handrails	303.13, 304.6, 702.9
Stairs and porches.....	702.9
Structurally sound	303.11
PORTABLE (TEMPORARY)	
Cooking equipment.....	603.2
Fire extinguishers.....	705.4
PRESSURE	
Water supply.....	505.3
PRIVATE, PRIVACY	
Bathtub or shower.....	503.1
Occupancy limitations	404.1
Required plumbing facilities	502
Sewage system	506.1
Water closet and lavatory.....	503.1
Water system.....	505.1
PROPERTY, PREMISES	
Access to public property	702.1
Cleanliness	303.1, 305.1
Condemnation	108.2
Definition.....	202

Demolition	110
Emergency measures	109
Exterior areas.....	302
Extermination, multiple occupancy .302.5, 306.4	
Extermination, single occupancy302.5, 306.3	
Failure to comply.....	110.3
Grading and drainage.....	302.2
Responsibility	301.2
Scope.....	301.1
Storm drainage.....	507
Vacant structures and land.....	301.3
PROTECTION	
Basement windows	303.18
Fire-protection systems	705
Signs, marquees and awnings.....	303.9
PUBLIC	
Access to public property	702.1
Cleanliness.....	303.1, 304.1
Egress.....	702.1
Hallway	502.3
Sewage system.....	506.1
Toilet rooms	503
Vacant structures and land.....	301.3
Water system	505

R

RAIN	
Basement hatchways	303.17
Exterior walls.....	303.6
Grading and drainage.....	302.2
Roofs.....	303.7
Window and door frames.....	303.14
RODENTS	
Basement hatchways	303.17
Condemnation.....	108.2
Exterior surfaces	303.6
Extermination	302.5, 306
Guards for basement windows	303.18
Harborage	302.5
Insect and rodent control.....	306.1
RECORD	
Official records	104.7
REHABILITATION	
Intent.....	101.3
REPAIR	
Application of other codes	102.3
Chimneys	303.12
Demolition	110.1
Emergency repairs	109.4
Exterior surfaces	303.2
Maintenance.....	102.2
Public areas	302.3
Signs, marquees and awnings.....	303.9
Stairs and porches	303.11
Weather tight.....	303.14

Workmanship.....	102.5
REPORTS	
Inspections.....	104.3
Test reports.....	105.3.3
RESIDENTIAL	
Extermination.....	306.5
Residential heating.....	602.2
Scope.....	101.2
RESPONSIBILITY	
Extermination.....	306
Fire safety.....	701.2
Garbage disposal.....	305.3
General.....	301.2
Mechanical and electrical.....	601.2
Persons.....	301.1
Placarding of structure.....	108.4
Plumbing facilities.....	501.2
Rubbish storage.....	305.2.1
Scope.....	101.2, 301.1
REVOKE, REMOVE	
Demolition.....	110
Existing remedies.....	102.4
Process ventilation.....	403.4
Removal of placard.....	108.6
Rubbish removal.....	305.2.1
RIGHT OF ENTRY	
Duties and powers of code official.....	104.4
Inspections.....	104.3
ROOF	
Exterior structure.....	303.1
Roofs.....	303.7
Storm drainage.....	507
ROOM	
Cooking facilities.....	403.3
Direct access.....	503.2
Habitable, light.....	402.1
Habitable, ventilation.....	403.1
Heating facilities.....	602
Light.....	402
Minimum ceiling heights.....	404.3
Minimum occupancy area requirements...	404.5
Minimum width.....	404.2
Overcrowding.....	404.5
Prohibited use.....	404.4.4
Separation.....	404.5.2
Sleeping.....	404.4
Temperature.....	602.5
Toilet.....	503
Ventilation.....	403
ROOMING HOUSES (See DORMITORY)	
RUBBISH	
Accumulation.....	305.1
Definition.....	202
Disposal.....	305.2
Garbage facilities.....	305.3.1

Rubbish storage.....	305.2.1
Storage.....	305.2.1

S

SAFETY, SAFE

Chimney.....	303.12
Condemnation.....	108.1
Electrical installation.....	605.1
Emergency measures.....	109
Fire safety requirements.....	701
Fireplaces.....	603.1
Intent.....	101.3
Safety controls.....	603.5
Scope.....	101.2
Temporary safeguards.....	109.2
Unsafe structures and equipment.....	108.1

SANITARY

Bathroom and kitchen floors.....	304.3
Cleanliness.....	303.1, 304.1
Disposal of garbage.....	305.3
Disposal of rubbish.....	305.2
Exterior property areas.....	302.1
Exterior structure.....	303.1
Food preparation.....	404.7
Controlled by occupant.....	302.1
Interior surfaces.....	304.3
Plumbing fixtures.....	504.1
Required plumbing facilities.....	502
Sanitation.....	304.1, 304.3
Scope.....	101.2

SASH

Window.....	303.14
-------------	--------

SCREENS

Insect screens.....	303.15
---------------------	--------

SECURITY

Vacant structures and land.....	301.3
---------------------------------	-------

SELF-CLOSING SCREEN DOORS

Insect screens.....	303.15
---------------------	--------

SEPARATION

Fire-resistance ratings.....	704
Privacy.....	404.1
Separation of units.....	404.1
Water closet and lavatory.....	503.1

SERVICE

Electrical.....	604.2
Method.....	107.3
Notices and orders.....	107.1, 108.3
Service on occupant.....	108.3

SEWER

General.....	506.1
Maintenance.....	506.2

SHOWER

Bathtub or shower.....	502.1
Rooming houses.....	502.2
Water heating facilities.....	505.4

Water system.....	505
SIGN	
Exit signs	702.5
Signs, marquees and awnings	303.9
SINGLE-FAMILY DWELLING	
Extermination.....	306
SINK	
Kitchen sink	502.1
Sewage system	506
Water supply.....	505.3
SIZE	
Habitable room, light.....	402
Habitable room, ventilation.....	403
Room area.....	Table 404.5
SLEEPING	
Area for sleeping purposes	404.4.1
Cooking facilities.....	403.3
SMOKE	
Detectors	705.5
SNOW	
Removal	302.3.1
SPACE	
General, light	402
General, ventilation.....	403
Occupancy limitations	404
Privacy.....	404.1
SPRINKLER	
Standpipe systems.....	705.3
STACK	
Chimneys.....	303.12
STAIRS	
Accumulations	703.1
Light.....	402.2
Exit facilities	304.5, 304.6, 702.9
Handrails	303.13, 304.6
Lighting	605.3
Public areas	302.3
Stairs and porches.....	303.11, 702.9
STANDARD	
Referenced	102.7
STORAGE	
Flammable matter	703.2
Food preparation	404.7
Garbage storage facilities	305.3
Rubbish storage facilities	305.2.1
Sanitation.....	305.1
STORY	
Number of exits.....	702.3
STRUCTURE	
Accessory structures.....	302.7
Closing of vacant structures.....	108.2
Definition.....	202
Emergency measures	109
General, exterior	303.1

General, condemnation	110
General, interior structure.....	304.1
Placarding of structure.....	108.4
Scope.....	301.1
Structural members	303.4, 304.2
Unlawful	108.1.4
Vacant structures and land.....	301.3
SUPPLY	
Combustion air	603.6
Connections	505.1
Water supply	505.3
Water system	505
Water heating facilities	505.4
SURFACE	
Exterior surfaces	303.2, 303.6
Interior surfaces.....	304.3
T	
TEMPERATURE	
Measurement	602.5
Nonresidential structures.....	602.4
Residential buildings	602.2
Water heating facilities	505.4
TENANT	
Definition	202
Scope.....	101.2
TEST, TESTING	
Agency	105.3.2
Methods	105.3.1
Reports	105.3.3
Required	105.3
TOXIC	
Process ventilation	403.4
TRASH	
Rubbish and garbage	305
TREAD	
Stair.....	303.11, 702.9

U	
UNOBSTRUCTED	
Access to public way	702.1
General, egress.....	702.1
UNSAFE	
Equipment.....	108.1.2
Existing remedies	102.4
General, condemnation	108, 110
General, demolition	110
Notices and orders	107, 108.3
Structure	108.1.1
USE	
Application of other codes	102.3
General, demolition	110

V

VACANT	
Closing of vacant structures.....	108.2
Emergency measure.....	109
Method of service	108.3
Notice to owner or to person responsible	107.1, 108.3
Placarding of structure	108.4
Vacant structures and land	301.3
VAPOR	
Exhaust vents	302.6
Process ventilation.....	403.4
VENT	
Connections.....	504.3
Exhaust vents	302.6
Flue, connected to	603.3
VENTILATION	
Clothes dryer exhaust.....	403.5
Combustion air.....	603.6
Definition.....	202
General, ventilation.....	403
Habitable rooms.....	403.1
Process ventilation.....	403.4
Recirculation	403.2, 403.4
Toilet rooms.....	403.2
VERMIN	
Condemnation	108.1.3
Insect and rodent control.....	302.5, 306
VIOLATION	
Abatement	106.5
Condemnation	108
General.....	106
Notice	107, 108.3
Penalty.....	106.4
Placarding of structure	108.4
Prosecution.....	106.3
Transfer of ownership	107.5
VOLATILE	
Flammable matter	703.2

W

WALK	
Sidewalks	302.3
WALL	
Accessory structures.....	302.7
Exterior surfaces.....	303.2, 303.6
Exterior walls	303.6
Foundation walls.....	303.5
General, fire-resistance rating	704.1
Interior surfaces	304.3
Outlets required	605.2
Temperature measurement.....	602.5
WASTE	
Accumulations	703.1
Disposal of garbage.....	305.3
Disposal of rubbish	305.2

Dwelling units.....	502.1
Flammable matter	703.2
Garbage storage facilities.....	305.3.1
WATER	
Basement hatchways	303.17
Connections	506.1
Contamination	505.2
General, sewage	506
General, storm drainage.....	507
General, water system.....	505
Heating.....	505.4
Hotels.....	502.3
Kitchen sink.....	502.1
Required facilities	502
Rooming houses	502.2
Supply	505.3
System	505
Toilet rooms	503
Water heating facilities	505.4
WEATHER, CLIMATE	
Heating facilities	602
Rule-making authority	104.2
WEATHERSTRIP	
Window and door frames.....	303.14
WEEDS	
Noxious weeds.....	302.4
WIDTH	
Minimum room width	404.2
WIND	
Weather tight.....	303.14
Window and door frames.....	303.14
WINDOW	
Emergency escape.....	702.12
Glazing.....	303.14.1
Guards for basement windows	303.18
Habitable rooms	402.1
Insect screens	303.15
Interior surface	304.3
Light	402
Openable windows	303.14.2
Toilet rooms	403.2
Ventilation	403
Weather tight.....	303.14
Window and door frames.....	303.14
WORKER	
Employee facilities, heat.....	503.3, 602.4
WORKMANSHIP	
General	102.

- Acronym ICC Code Name
IBC International Building Code
ICCEC ICC Electrical Code
ICCPC ICC Performance Code
IEBC International Existing Buildings Code
IECC International Energy Conservation Code
IFC International Fire Code
IFGC International Fuel Gas Code

IMC International Mechanical Code
IPC International Plumbing Code
IPMC International Property Maintenance Code
IPSDC International Private Sewage Disposal Code
IRC International Residential Code
IUWIC International Urban-Wildland Interface Code
IZC International Zoning Code



Property Maintenance Code

The Village of Ashville is a great place to live because village residents take pride in their homes and neighborhoods. To keep the village looking great, the village has adopted ordinances regulating property maintenance in both residential and commercial areas.

The Village's Code Enforcement Officer responds to complaints regarding property maintenance and regularly patrols the Village to identify violations. When property maintenance violations are identified, enforcement action is taken. This can include warnings and Notices to Appear in Mayor's Court.

Reporting a Code Violation

If you think a property in your neighborhood is not being maintained in compliance with Village Codes, contact the Code Enforcement Officer at 740-983-3112 or send e-mail to VCEO@ashvilleohio.net.

Upon receiving the complaint, the Village Code Enforcement Officer will perform an inspection of the property. If violations are observed, the owner/resident will be notified of the violation and instructed to correct the violation(s).

Read our list of the [most common property maintenance violations](#).

When reporting a code violation, provide the following information to help the Village Code Enforcement Officer respond to your complaint:

- Provide the exact address of the alleged violation.
- Clearly describe the violation you observed at the address.
- Your name, address, and telephone number. This will allow the Village Code Enforcement Officer to contact you if further information about your complaint is required.

The Code Enforcement Process

When a violation is identified, the owner/resident will be notified of the violation and given an opportunity to correct it.

Depending on the type of violation, the estimated cost of bringing the property into compliance, and the past history of code violations at the property, the owner/resident will be given up to 30 days to bring the property into compliance with Village Codes.

If violations are not corrected in the time determined by the Village Code Enforcement Officer, a [Notice to Appear in Mayor's Court](#) (ticket) may be issued. When this occurs, the owner/resident must appear in Court.

Upon conviction in Mayor's Court, violators may be required to pay fines. If time in jail is necessary that would be referred to Municipal Court.

In some situations (tall weeds and grass, immediate hazards) the Village may make arrangements to have the violation abated. When this occurs, the property owner must pay for the costs of abatement. If the property owner fails to do so, Village will place a special assessment against the property.

Most Common Property Maintenance Violations

If you think a property in your neighborhood is not being maintained in compliance with Village Codes, contact the Village Code Enforcement Officer at 740-983-3112 or send e-mail to VCEO@ashvilleohio.net.

Maintenance of Structures

- Paint - Peeling paint on wall surfaces, trim, windows, etc. shall not exceed 25%.
- Foundations - Foundations must remain structurally sound, free from open cracks or breaks so as to prevent the entry of rats and other animals.
- Exterior Openings - All exterior openings shall be fitted with window, door, or other appropriate covering and shall be maintained in good condition.
- Windows - Windows shall be fully supplied with glass windowpanes without open cracks or breaks, or a substitute material approved by the Village.
- Gutters and Downspouts - Guttering and downspouts that have been broken or damaged shall be repaired or replaced.
- Attached Structures - Attached structures such as porches, stairs, landings, etc. shall be maintained in good condition.
- Fences - Fences shall be properly maintained in good condition free of damage, breaks, or missing structural members.
- Driveways - Driveways, walkways, etc. shall not be allowed to deteriorate to the extent they constitute a safety hazard.

Lawn Maintenance

- Weeds - Grass and weeds shall not exceed ten (10) inches in height. This includes public rights-of-way and easement areas.
- Trees - Trees shall be trimmed to a minimum height of fourteen (14) feet above the street and nine (9) feet above the sidewalk.
- Bushes - Bushes, hedges, trees, etc. shall be trimmed in such a manner as to not obstruct a public sidewalk or intersection.

Outside Storage

- Useful Items - All items stored outdoors must be located within a fully enclosed structure, or within the back yard and fully screened from view from any adjacent property. In no event shall outside storage occupy more than 20% of the allowable outside storage area.
- Trash & Debris - The throwing, leaving, depositing, or allowing the accumulation of any worn out, broken, or worthless item, waste, garbage, trash, debris, or refuse on any property, drainage course or other land is prohibited.
- Trash Cans - Trash cans and recycling bins must be stored indoors, or in the side or rear yard screened from view.

Vehicle Parking & Storage

- Hard Surfaces - All vehicles must be parked on a hard surface (concrete or asphalt) Parking on unimproved surfaces is not permitted.
- Inoperable/Unlicensed Vehicles - All vehicles stored on private property must be operable and property licensed unless stored in an enclosed structure.

- Recreational Vehicles - Recreational vehicles, including boats, campers, trailers, etc. must be stored in the side or rear yard, at least five feet from the property line and 15 feet from the street (corner lots.) Recreational vehicles may be stored in the front driveway for no more than seventy-two (72) hours in any fourteen (14) day period.
- **Commercial Vehicles** - Commercial vehicles may not be permanently parked in residential areas.